TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 700571

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only, T32-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 19 Page(s) 8291)

Set an ironstone 15x15x5 ins., 10" in ground for cor. of secs. 1, 6, 7 and 12, marked with 1 notch on the N. and 5 notches on the S. edges, from which

A Fir 20" dia., bears N.63°E., 29 lks. dist.mkd. T32S R2W S6 BT.
A Fir 12" dia., bears S.85°E., 43 lks. dist. mkd. T32S R2W S7 BT.
A Matherone 12" dia., bears S.50°W., 25 lks. dist. mkd. T32S R3W S12 BT.
A Pine 18" dia., bears N.83°W., 17 lks. dist. mkd. T32S R3W S1 BT.

Tied corner in GLO survey by Fred Mensch, Contract #757, dated Sept. 14, 1904 - DCSO records, Vol. 20 Pg. 8384

"I destroy marks on former corner bearing trees referring to secs. 1 and 12"

Survey by Glenn S. Baughman - For: U.S. Forest Service - Aug. 1968 - C.S. File 55/87-5

Found - Ironstone 15x15x5" with 1 notch on N. and 5 notches on S.
Orig. 20" now 32" Fir bears N.61°E., 18.5 ft. mkd. T32S R2W S6 BT.
Orig. 12" now 26" Fir bears S.86°E., 24.5 ft. mkd. T32S R2W S7 BT.

Set 2" x 30" I.P. with brass cap stamped: T 32 S
R3W S12 | S 6 / S 7 ~~CC~~ R2W
1968
OLS 536

Placed BT tags on both original BTs and facing monument.
(Note: BLM letter in C.S. File states that they would not call this a closing corner.)