

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec Cor for 1 & 12 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 20 Page(s) 8384)

Set a granite stone 18x14x4 ins., 12" in the ground, for closing cor. of secs. 1 and 12, marked CC on W. and 1 groove on N. and 5 grooves on S. face, from which
A Pine 9" dia., bears N.80°W., 84 lks. mkd. T32S R3W S1 BT
A Red Fir 20" dia bears S.23°W. 86 lks mkd T32S R3W S12 BT
I destroy marks on former corner bearing trees referring to these sections.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - May 1, 1958 - C.S. File 42/356-5

Determined by O.B.T.:
28" Fir bears S.23°W., 56.7 ft., found scribe. This tree is being removed for new road construction.
At corner point found original stone and SET iron pipe, from which
12" Fir bears N.3°W., 6.8 ft. mkd. S1 T32S BT.
9" Fir bears S.84°W., 14.6 ft. mkd. S12 T32S R3W BT.
Road bears South 56.0 ft. dist.

Survey by Glenn S. Baughman - For: U.S. Forest Service - Aug. 1968 - C.S. File 55/87-20

Found - 18x14x4" stone mkd. with 1 notch on N. & 5 notches on S. faces.
Axle 1½" x 30".
16" Fir with open face, scribes in good condition, N.3°W., 6.8 ft.
12" Fir with closed face bears S.84°W., 14.6 ft.
Set 2" x 30" I.P. with brass cap stamped:
T 32 S
R3W CC $\frac{S 1}{S 12}$ | S 6 R2W
1968
OLS 536

From the pipe monument, the BTs are:
16" Fir bears N.3°W., 6.8 ft.
12" Fir bears S.84°W., 14.6 ft.
Placed BT tags on all BTs and facing monument.

See C.S. File 63/166, T32S R3W folder, for 2005 correspondence between USFS & the BLM concerning the subdivision of Secs 1 & 12. This files are not available on the internet.