

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 987030

PRIMARY CORNER DESCRIPTION Corner No. 3 of HES #186, Tract A

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 186 by Frederick W. Rase, surveyor, under special instructions dated Feb. 3, 1916 - Surveyed Sept. 1916 - DCSO records Vol. 34 Page(s) 14065

Cor. No. 3, on line bet. cors. 1 & 2 of List 6-422
Set a serpentine stone 26x12x10", 16" in the ground, over a stone mkd. with a cross for cor. No. 3 of this survey, mkd. 3 HES 186 on side facing the claim, from which
 A fir, 36" dia., bears N.44°00'W., 17 lks., mkd: X 3 HES 186 BT.
 A fir, 24" dia., bears S.56°00'W., 30 lks., mkd: X 3 HES 186 BT.
Raised a mound of earth 4 ft. base, 2 ft. high, 3½ ft. within the claim.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - Dec. 29 1969 - C.S. File 54/91-89

Found - Old Corner Stone, in place, mkd: "+" on top & "3HES186" on side.
 Orig. 36", now 40" Fir, N.44°W. 11.2 ft. now decayed stump, we open & find frag. scribe.
 Orig. 24", now 30" Fir, S.56°W. 19.8 ft., now decaying stump, we open & find "3 HES 186 BT" scribe.
Set - Brass Cap at Cor. Mkd: County Surveyors T32S R3W (Reset Stone Alongside) Office, 1969 Cor.#3 | HES 186
New BTs- 7" W.Fir S.13°W. 25.7 ft. mkd: "3 HES 186 CS BT"
 7" W.Fir N.24°W. 24.3 ft. mkd: "3 HES 186 CS BT"
This corner lies on flat end of old fence, course E.

Fd. Ok 6/2/1982 - USFS - C.S. File 61/32-20