

PRIMARY CORNER DESCRIPTION Corner No. 5 HES 186, Tract A

Alias	Description
Alias	Description
Alias	Description
Alias	Description

HES No. 186 by Frederick W. Rase, surveyor, under special instructions dated Feb. 3, 1916 - Surveyed Sept. 1916 - DCSO records Vol. 34 Page(s) 14066

Cor. No. 5

Set a granite stone 25x12x5", 15" in the ground, over a stone mkd. with a cross for cor. No. 5 of this survey, mkd. 5 HES 186 on side facing the claim, from which

A fir 24" dia., bears N.42°40'W., 24 lks., mkd X 5 HES 186 BT.

A fir 14" dia., bears S.54°45'W., 23 lks., mkd X 5 HES 186 BT.

Raise a mound of earth 4 ft. base, 2 ft. high 3½ ft. dist. within the claim.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - Dec. 30, 1969 - C.S. File 54/91-93

Found - Old corner stone, in place, mkd "5HES186" on side. Orig. 24" Fir N.42°40'W., 15.8 ft. now stump, broken off almost at ground level, no scribe found. Orig. 14" now 22" Fir S.54°45'W., 15.2 ft. alive, shows good scar, we tag.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T32S R3W (reset stone alongside) OFFICE 1969 COR #5 \HES 186

New BTs- 14" D.Fir S.15°E., 24.5 ft mkd: "5 HES 186 CS BT" This corner lies on gentle Northerly slope.

Leonard Herzstein, USFS - Jim Landrum - June 10, 1982 - C.S. File 61/32-22

Found - 1969 County brass cap properly mkd. firmly set, projecting 12" above ground. Orig. 22" D.Fir S.54°45'W., 15.2 ft. with healed blaze.

Orig. D.Fir root crown, size indeterminate N.42°40'W., 15.8 ft. with no marks visible. 1969 14" D.Fir S.15°E., 24.5 ft. with healed blaze.

Set - Add 2 ft. dia., mound of stone, IP now projects 6" above mound of stone.