

PRIMARY CORNER DESCRIPTION Corner No. 6 HES 186, Tract A

Alias	Description

HES No. 186 by Frederick W. Rase, surveyor, under special instructions dated Feb. 3, 1916 - Surveyed Sept. 1916 - DCSO records Vol. 34 Page(s) 14066

Cor. No. 6, on a prolongation of the line bet. cors. 4 & 3 of List 6-969

Set a granite stone 24x15x10", 14" in the ground, over a stone mkd. with a cross for cor. No. 6 of this survey, mkd. 6 HES 186 on side facing the claim, from which

 A fir 40" dia., bears S.80°45'E., 87 lks., mkd X 6 HES 186 BT.

 A fir 14" dia., bears S.3°45'W., 144 lks., mkd X 6 HES 186 BT.

Raise a mound of earth 4 ft. base, 2 ft. high 3½ ft. dist. within the claim.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - Dec. 30, 1969 - C.S. File 54/91-94

Found - Old Corner Stone, in place & mkd: "+" on top & "6HES186" on side

 Orig. 40", now 44" Fir, S.80¾°E. 57.4 ft., now stump, scribe "186" visible on open blaze.

 Orig. 14", now 26" Fir, S.3¾°W., 75.2 ft. alive, shows good scar, we tag.

Set - Brass Cap at Cor. mkd: County Surveyors T32S R3W (Reset Stone Alongside) Office, 1969 Cor.#6\ HES 186

New BTs- 12" D.Fir N.4°E. 12.3 ft. mkd: "6 HES 186 CS BT"

 12" W.Fir N.74°E. 8.8 ft. mkd: "6 HES 186 CS BT"

This corner lies on flat approx. 100 ft. East of Applegate Creek, course N.10°W.

Fd. Ok by L. Herzstein, USFS, 4/21/1982 - (Orig. 14" BT is now in roadway) - C.S. File 61/32-23

1