

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 987080

PRIMARY CORNER DESCRIPTION Corner No. 8 HES 186, Tract A

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

HES No. 186 by Frederick W. Rase, surveyor, under special instructions dated Feb. 3, 1916 - Surveyed Sept. 1916 - DCSO records Vol. 34 Page(s) 14067)

Cor. No. 8
Set a granite stone 24x9x6", 14" in the ground, over a stone mkd. with a cross for cor. No. 8 of this survey, mkd. 8 HES 186 on side facing the claim, from which
 A fir, 30" dia., bears S.13°00'W., 23 lks., mkd: X 8 HES 186 BT.
 A fir, 28" dia., bears N.72°03'E., 46 lks., mkd: X 8 HES 186 BT.
Raise a mound of earth 4 ft. base, 2 ft. high 3½ ft. dist. within the claim.

Douglas Co. Surveyors Office - Clell Goodwin - Vic Cangie - Lenora Ladig - 6/12/1975 - C.S. File 57/30-8

Found - 30" Fir stump with visible scribe "BT" on NE face bears S.13°W., 15.2 ft.
 Rotted stump with no visible scribe bears N.72°E., 30.4 ft. No sight of original stone.
New - Set Brass cap on 1½" Iron Pipe stamped
 Douglas Co Surveyor T32S R3W
 1975 Cor 8
 +
 HES 186
From Which -
 A 8" Pine scribed "T32S R3W 8 HES 186 CS BT" in a double blaze bears S.89½°E., 19.1 ft.
 A 10" Pine scribed "T32S R3W 8 HES CS BT" in a double blaze bears S.28°W., 15.4 ft.
Compass Declination 20°