

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 987110

PRIMARY CORNER DESCRIPTION Corner No. 11 HES 186, Tract B

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

HES No. 186 by Frederick W. Rase, surveyor, under special instructions dated Feb. 3, 1916 - Surveyed Sept. 1916 - DCSO records Vol. 34 Page(s) 14068-9

Cor. No. 11

Set a conglomerate stone 24x12x7", 14" in the ground, over a stone mkd. with a cross for cor. No. 11 of this survey, mkd. 11 HES 186 on side facing the claim, from which

A fir 26" dia., bears N.12°02'W., 36 lks., mkd: X 11 HES 186 BT"

A fir, 28" dia. bears N.83°32'W., 31 lks., mkd: X 11 HES 186 BT"

Raised a mound of earth 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

Douglas Co. Surveyors Office - Clell Goodwin - Gary Langlitz - Vic Cangie - Lenora Ladig - No Date on Corner renewal but it is in the July/Aug 1975 folder - C.S. File 57/34

Found - Orig. W.N.W. BT, is now 26" stump with scribed "X 11 HES 186 BT" visible, bears N.83½°W., 20.5 ft.
Orig. N.N.W. BT is blown down, center of hole left by roots, bears N.12°W., 23.8 ft.
No sign of orig. stone.

Set - Brass cap stamped, DOUGLAS COUNTY SURVEYOR T32S R3W
1975 Cor 11
+
HES 186

At corner from which:

A 8" Pine, scribed "T32S R3W 11 HES 186 CS BT" in a double blaze, bears S.26½°E., 28.8 ft. (Note: scribe is on the west face of the tree)

A 8" Fir, scribed "T32S R3W 11 HES 186 CS BT" in a double blaze, bears N.64½°W., 41.7 ft. (Note: scribe is on SE face but does not face corner)

A brass cap stamped "Douglas County Surveyor, T32S R3W Cor 8 + HES 186 1975, bears S.43°E., 26.9 ft.

Compass declination 20°.