

TOWNSHIP 32 RANGE 03 POINT IDENTIFIER # 987130

PRIMARY CORNER DESCRIPTION Corner No. 13 HES 186, Tract B

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

HES No. 186 by Frederick W. Rase, surveyor, under special instructions dated Feb. 3, 1916 - Surveyed Sept. 1916 - DCSO records Vol. 34 Page(s) 14069

Cor. No. 13 on line bet. cors. 4 & 5, List 6-422
Set a diorite stone 24x18x7", 14" in the ground, over a stone mkd. with a cross for cor. No. 13 of this survey, mkd. 13 HES 186 on side facing the claim, from which
 A fir, 30" dia., bears S.22°00'W., 77 lks., mkd: X 13 HES 186 BT.
 A fir, 18" dia., bears N.75°40'E., 60 lks., mkd: X 13 HES 186 BT.
Raise a mound of earth 4 ft. base, 2 ft. high, 3½ ft. within the claim.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - Dec. 30, 1969 - C.S. File 54/91-91

Found - Corner Stone in place, mkd. "+" on top & "13HES186" as called for.
 Orig. 30", now 32" Fir, S.22°W. 50.8 ft., now stump, we open & find "S 186 B" scribe.
 Orig. 18", now 26" Fir, N.75°40'E. 39.6 ft., now stump, we open & find burned blaze, no scribe.
Set Brass Cap at Cor. mkd: County Surveyors T32S R3W
 (Reset Stone Alongside) Office 1969 Cor.#13 } HES 186
New BTs- 6" D.Fir S.87°W. 18.0 ft. mkd: "13 HES 186 CS BT"
 6" Laurel N.54°E. 8.8 ft. mkd: "13 HES 186 CS BT"
This corner lies on moderate S.E. slope in very dense Manzanita, Rhododendron, & Chinquapin brush.