

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 100169

PRIMARY CORNER DESCRIPTION E. Sec Cor for 25 and 36 only, T32-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 (DCSO records Vol. 20 Page(s) 8591)

I destroyed all marks referring to secs. 25 and 36, and at my point of intersection, I set a Yew post, 3 ft. long, 4" sq., 24" in the ground for closing corner of secs. 25 and 36, marked C C T32S R5W on W.; S25 on N.; and S36 on S. faces, with 1 groove on S. and 5 grooves on N. faces, from which
A Fir 40" dia., bears S.10°W., 70 lks. mkd. T32S R5W S36 BT.
A Yew 10" dia., bears N.24°W., 55 lks. marked T32S R5W S25 BT.

George J. Wenderoth - Nov. 7, 1956 - C.S. File 47/139

Found - Old original stake still in ground. Renewed stake
Stump of 40" Fir S.10°W., 46.2 ft., no marks.
Burnt Yew stump N.24°W., 36.3 ft. no marks.
Scribed -8" Fir S.10°25'W., 15.0 ft.
12" Fir N.37°57'W., 39.7 ft.

Milo E. Godfrey, Deputy - Wit: Mike Stone - June 1964 - C.S. File 53/52-60

Found - Yew wood stake set by Wenderoth, scribed "CS".
D.Fir now 15" dia., N.38°W., 39.7 ft., to face,.
Both axe scars very plain, but healed over. Tree in good condition.
Wenderoth's SW tree is now dead and down, scribing visible.
Stump of orig. SW tree and burned remains of orig. NW tree.

Set Brass cap at cor. mkd: County Surveyors Office
T 32 S R 5 W
CC S 25 | R 4 W
S 36 |
1964

Reset Yew post alongside.
New BT - 5" W.Fir S.73°W., 14.0 ft. mkd. CC S36 CS BT.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #977 Surveyed, May/June 1979 - (DCSO records Vol. 43 Page(s) 16763)

CORNER REPORT ONLY
(Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 100169

PRIMARY CORNER DESCRIPTION CC for Secs. 25 and 36, T32-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The original closing cor. of secs. 25 and 36, perpetuated and recorded by Godfrey in 1964, monumented with a galv. iron pipe, 1" dia., firmly set, projecting 14" above ground, with brass cap properly marked.

from which the remains of the original bearing trees:

A sawed and decayed Fir stump, 40" dia., bears S.11°W., 73½ lks. dist., no marks remaining. (Rec. S.10°W., 70 lks.)

A roothole bears N.23°W., 53 lks. dist., alongside of which is lying a burned and decayed Yew 10" dia., no marks remaining. (Rec. N.24°W., 55 lks.)

and a bearing tree mkd. by Wenderoth in 1956:

A Fir 16" dia., bears N.36¼°W., 60 lks. dist., with healed blaze.

and a bearing tree mkd. by Godfrey:

A W.Fir 9" dia., bears S.71½°W., 21 lks. dist., with healed blaze.