

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION W. C. C. for Secs. 30 and 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 12" dia., bears N.13½°E., 63½ lks. dist., mkd. T32S R4W S30 CC BT.

A Fir 6" dia., bears S.24½°E., 6¼ lks. dist., mkd. S R4W S31 CC.

From the same point, the original closing cor. of secs. 30 and 31, bears N.89°47'W., 0.18 chs. dist.,perpetuated and recorded by Godfrey in 1964, monumented with a galv. iron pipe, 1" dia., firmly set, projecting 13" above ground, with marked brass cap.

from which the remains of the original bearing trees

A burned and rotted Fir stump 12" dia., bears N.48°E., 20 lks. dist., with scribe marks S R4W visible on portion of burned blaze.

A Madrone 13" dia., bears S.62°E., 37 lks. dist., with decayed blaze.

and bearing trees mkd. by Godfrey:

A Madrone 13" dia., bears N.7¼°E., 25 lks. dist., with scribe marks T32S R4W S30 CC BT visible on partially healed blaze.

A Fir 6" dia., bears S.73°E., 20½ lks. dist., with healed double blaze.

A Live Oak 18" dia., bears S.8°W., 30¼ lks. dist., with illegible scribe marks visible on partially healed double blaze.