

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T32-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Butler Ives and George W. Hyde, under Contract #39, dated January 4, 1854 - (DCSO records Vol. 20 Page(s) 8453)

-----  
Set post corner of secs. 18, 19, 13 and 24, from which  
A Laurel 10" dia., bears N.14°W., 61 lks.  
A Laurel 4" dia., bears N.16°E., 71 lks.  
A Laurel 4" dia., bears S.88°E., 23 lks.  
A Fir 30" dia., bears S.45°W., 34 lks.

Douglas Co. Surveyors Office - George J. Wenderoth, Deputy -  
Wit: Clifford Worley - Oct. 1946 - C.S. File 39/158

-----  
Find old BT badly rotted.  
Drive 5/8" Bolt for corner.  
Scribe - 8" Fir S.23°45'E., 13.2 ft.  
6" Chinquapin S.46°40'W., 25.0 ft.  
6" Chinquapin N.51°16'W., 8.0 ft.

Survey by Richard Templin Jr. - For: Sierra Land Co. - April 30, 1956 - C.S File 42/133

-----  
Found - 1" Iron rod  
Stump of 20" Fir, S.45°W., 34 lks.  
8" Chinquapin N.55°W., 8.2 ft.  
12" Fir S.22°E., 13.5 ft., blaze healed.  
New BT - 8" Fir N.09°W., 8.6 ft. mkd. S13 RE 3024 BT.

Fd. OK, James Artman, March 16, 1990, M 109-66

BLM Resurvey by Lynn Roseberry, Cadastral Surveyor - Group #977 - Surveyed, May/June 1979 (DCSO records, Vol. 43 Page 16767)

-----  
The Sec. Cor. perpetuated and recorded by Wenderoth in 1945, monumented with an iron rod 1" dia., firmly set, projecting 6" above ground, from which the remains of an original bearing tree  
A decayed Fir stump 20" dia., bears S.45°W., 34 lks. dist., with no marks remaining.  
and bearing trees mkd. by Wenderoth  
A Fir 16" dia., bears S.23 3/4°E., 20 lks. dist. with healed double blaze.  
A Chinquapin 9" dia., bears S.44 3/4°W., 38 lks. dist. with scribe marks S24 visible on partially healed double blaze.

(Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T32-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Chinquapin 9" dia., bears N.55°W., 12½ lks. dist., with scribe marks BT visible on partially healed double blaze.

and a bearing tree mkd. by Templin in 1956

A Fir 13" dia., bears N.9°W., 13 lks. dist. with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 23 ins. in the ground, directly over the iron rod, with brass cap marked

T 32 S

R 5 W R 4 W

S 13 S 18

S 24 S 19

1979

from which a new bearing tree

A Fir 14" dia., bears N.67½°E., 15½ lks. dist. mkd. T32S R4W S18 BT.