

PRIMARY CORNER DESCRIPTION N. 1/16 Cor. bet. Sec. 7; & 12 of T32-5

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Survey by G.G. Stewart, Deputy - For: Wilson; Neff; Payne; Booth; etal - May 1922 - Vol. 3 Pg. 121; M 3-32 and C.S. File 45/186

-----  
Set 1" I.Pipe.  
20" Fir N.80°W., 6.2 ft.

Survey by Marvin C. Ramsey - For: A. Cripps - June 8, 1967 - C.S. File 55/37 and M 34-26

-----  
Set at 1320 ft. which is the proportionate distance.  
There is no iron pipe and the 20" Fir which bears N.80°W., 6.2 ft. is now a sawed stump and scribe marks destroyed.  
Set 1" Iron pipe 3 ft. long, 28" in the ground, mkd. RS404, from which  
10" D.Fir bears N.10½°E., 14.6 ft. mkd. N 1/16 S7 RS404 BT  
20" D.Fir bears S.80°W., 20.2 ft. mkd. N 1/16 S12 RS404 BT

BLM resurvey by Larry Evans, Cadastral Surveyor under Group #736, surveyed May/June 1971 (DCSO recs Vol. 37 Page 15331)

-----  
The N 1/16 sec. cor. of secs. 7 & 12, established & recorded by Stewart, in 1922; subsequently perpetuated and recorded by Ramsey in 1967, monumented with an iron pipe, 1" dia., protruding 6" above the ground, firmly set, with attached washer mkd. RS404 from which the remains of the bearing tree mkd:

- A sawed fir stump, 20" diam., bears S.86¾°W., 9 lks., no marks remaining.
- and bearing trees mkd. by Ramsey
  - A fir, 10" dia., bears N.10½° E., 22 lks., with pitched over blaze.
  - A fir, 20" dia., bears S.80°W., 30½ lks., with pitched over blaze.

At the corner point  
Set an iron post 28" long, 2½" dia., 24" in the ground, directly over the iron pipe, with brass cap mkd.

N 1/16  
S 12 | S 7  
1971