

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T32-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Butler Ives and George W. Hyde, under Contract #39, dated January 4, 1854 - (DCSO recs Vol. 20 Page(s) 8451)

-----  
Set post cor. of secs. 6, 7, 1 and 12, from which  
A Y.Pine 36" dia., bears N.55°E., 40 lks.  
A B.Oak 12" dia., bears S.31°E., 76 lks.  
A B.Oak 10" dia., bears S.38½°W., 102 lks.  
A B.Oak 12" dia., bears N.41½°W., 170 lks.

Survey by G.G. Stewart, Deputy Co. Surveyor - May, 1922 - Vol. 3 Page 121 and M 3-32 and C.S. File 45/186

-----  
Set an iron pipe from 2 O.B.T.s Others gone.  
Marked - 30" Pine N.54½°E., 26.8 ft. (O.B.T.)  
10" B.Oak S.30°E., 47.4 ft.  
20" B.Oak N.5°W., 95.2 ft.  
18" B.Oak S.44°W., 121.0 ft.

Survey by John H. Markham, Jr. - Wit: Martin Perry - May 14, 1951 - C.S. File 40/312-1

-----  
Determined by O.B.T.  
A B.Oak 14" dia., bears S.31°E., 50.0 ft. (O.B.T.)  
At corner point found 12x12x14 stone and 3/4" iron pipe, from which  
A Pine 5" dia., bears S.85°W., 8.0 ft. mkd. XXX BT.  
A Pine 12" dia., bears N.21°W., 12.0 ft. mkd. XXX BT.  
A B.Oak 15" dia., bears N.83°E., 62.4 ft. mkd. S6 2880 BT

Survey by George Wenderoth - August 1951 - C.S. File 41/18 and M 3-9

-----  
Found - 3/4" Iron pipe.  
16" B.Oak S.30°E., 47.4 ft.  
20" B.Oak N.81°40'E., 61.6 ft. mkd. 2880  
24" B.Oak N.5°W., 95.2 ft.  
Other trees blazed but not scribed.

Survey by Marvin C. Ramsey - Wit: R. Darrig - For: A Cripps - June 8, 1967 - C.S. File 55/37 and M 34-26

-----  
Found - 1" Iron pipe 4" above ground, firmly set. Remains of a pipe burned out, bears N.54°E., 26.8 ft.  
24" B.Oak bears S.80°E., 47.4 ft., healed.  
24" B.Oak S.44°W., 121.0 ft. with marks burned out.  
30" B.Oak bears N.5°W., 95.2 ft., healed.  
(Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; & 1 & 12 of T32-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs -Yellow Pine, 10" dia., bears N.44°E., 17.7 ft.  
marked "T32S R4W S6 RS 404 BT"  
Yellow Pine, 12" dia., bears S.37°W., 57.3 ft.  
marked "T32S R5W S12 RS 404 BT"

BLM resurvey by Larry D. Evans, Cadastral Surveyor under Group #736, Surveyed May/June 1971 (DCSO records Vol. 37 Page(s) 15331-32)

-----  
The Sec. cor., perpetuated and recorded by Stewart in 1922, from two orig. 1854 bearing trees, monumented with an iron pipe 1" dia., protruding 4" above ground, firmly set, alongside of which is lying a basalt stone reported by Markham in 1951, 16 x 12 x 10 ins., with no marks visible, at record bearing from the remains of the original 1854 bearing trees:

A burned out Ponderosa Pine stump, size indeterminate, bears N.55°E., 40 lks. dist. no marks remaining.

A B.Oak 18" dia., bears S.31°E., 76 lks. dist., with healed double blaze.

A B.Oak 20" dia., bears N.41½°W., 161 lks. dist., with opened and decayed double blaze with negative scribe marks BT visible on detached piece lying alongside. (Rec. 170 lks.)

and bearing trees mkd. by Stewart:

A B.Oak 22" dia., bears S.44°W., 183½ lks. dist. with knife marks S12 BT visible on opened and decayed blaze.

A B.Oak 23" dia., bears N.3 3/4°W., 149 lks. dist. with healed blaze.

and bearing trees mkd. by Markham:

A B.Oak 20" dia., bears N.82½°E., 95½ lks. dist., no marks visible on partially opened and decayed blaze.

A Ponderosa Pine 12" dia., bears N.22¼°W., 19½ lks. dist., with healed blaze.

and bearing trees mkd. by Ramsey in 1967:

A Ponderosa Pine 11" dia., bears N.44°E., 26½ lks. dist. with pitched over blaze.

A Ponderosa Pine 13" dia., bears S.37°W., 85½ lks. dist. with pitched over blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, directly over the iron pipe, with brass cap marked:

T 32 S	
R 5 W	R 4 W
S 1	S 6
S 12	S 7
1971	

cont.

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM Dependent resurvey by Arthur R. Rambo, Cadastral Surveyor under Group No. 2707, surveyed April/May 2013 - (DCSO records, Vol. 58 Page(s) 23128-9)

-----  
The cor. of secs. 1, 6, 7, & 12, on the E. bdy. of the Tp., monumented with an iron post, 2½" dia. firmly set, projecting 4" above the ground, with brass cap (properly) mkd.

- from which the remains of original bearing trees
  - An oak snag, 19" dia., bears S.31°E., 48.7 ft., with a healed blaze. (Record, 50.2 ft.).
  - An oak snag, 17" dia., bears N.41½°W., 104.4 ft., with no scribe marks visible on open blaze. (Record, 106.3 ft.)

- and the remains of BTs mkd. by Stewart, in 1922
  - A root hole with down oak alongside, 20" dia., bears S.44°W., 121.1 ft., with no scribe marks visible on open blaze.
  - An oak snag, 21" dia., bears N.3¾°W., 98.3 ft., with a healed blaze.

- and the remains of BTs mkd. by Markham, in 1951
  - A root hole with down oak alongside, size indeterminate, bears N.82½°E., 63.0 ft., no marks visible.
  - A root hole with down pine alongside, indeterminate size, bears N.22¾°W., 12.9 ft., with illegible scribe marks visible on open blaze.

- and a bearing tree mkd. by Ramsey, in 1967
  - A pine, 19" dia., bears S.37°W., 56.4 ft., with a healed blaze.

- and new bearing trees
  - A fir, 8" dia., bears N.31½°E., 47.6 ft., mkd. X at breast height, and BT at base.
  - A fir, 8" dia., bears S.67¼°E., 10.4 ft., mkd. X at breast height, and BT at base.
  - A fir, 10" dia., bears N.82°W., 51.7 ft., mkd. T32S R5W S1 BT.

Daniel Baker - For: Weyerhaeuser - 7/2019 - M176-18A-C

- 
- Found - ¾" BLM brass cap "1971"
  - 8" Fir, N.31°E., 48.4' (rec. = N.31½°E., 47.6') to nail side/center-2013 BLM BT
  - 9" Fir, S.66°E., 10.6' (rec.- S.67¼°E., 10.4' to nail side/center - 2013 BLM BT
  - 19" Pine, S.36°W., 57.2' (rec. = S.37°W., 57.3) to nail side/center-M34-26 BT
  - 11" Fir, N.82°W., 52.0' (rec. = N.82°W., 51.7') to nail side/center-2013 BLM BT