

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 120500

PRIMARY CORNER DESCRIPTION W. 1/16 cor. between Secs. 7 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

George J. Wenderoth, Deputy Co. Surveyor - For: Fred H. Daugherty - 1953 - C.S. File 45/136

Set 1" Iron bar.
5" Chinquapin S.86°14'E., 34.5 ft.
8" Madrona N.13°42'E., 20.2 ft.

BLM resurvey by Larry Evans, Cadastral Surveyor under Group #736, surveyed May/June 1971 (DCSO records Vol. 37 Page(s) 15337-38)

(CORNER REPORT ONLY)

Intersect a point established and recorded by Wenderoth in 1953, monumented with an iron bar, 1" dia., protruding 4" above ground, firmly set, from which bearing trees mkd. by Wenderoth:

A shattered Madrone stump 8" dia., bears N.13 3/4°E., 30 lks. dist., alongside of which is lying a madrone, with scribe marks 1/16 S7 CS BT visible on open blaze.

A shattered Chinquapin stump, 8" dia., bears S.86¼°E., 52½ lks. dist., with scribe marks 1/16 18 CS BT visible on open and decayed blaze.