

PRIMARY CORNER DESCRIPTION NW 1/16 Cor. Section 7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Douglas Co. Surveyors Office - G.G. Stewart, Deputy - May 1922 - M 3-32 - Vol. 3 Page 121 - C.S. 45/186

-----  
Set - Iron Pipe & scribed a 12" Ash S.55°W., 37.5'.

Survey by Marvin C. Ramsey - Wit: R. Darrig - For: A. Cripps - June 8, 1967 - C.S. File 55/37 and M 34-26

-----  
Do not find an iron pipe at this corner so determine the corner point from a BT. See M 3-32

18" Ash bears S.55°W., 37.5 ft. with scribe marks 1/16 BT exposed.

Set 1" iron pipe 3 ft. long, 28" in the ground, mkd. RS 404, from which new bearing tree:

14" Cedar bears S.11°W., 30.3 ft. mkd. NW 1/16 S7 RS 404 BT.

BLM resurvey by Larry Evans, Cadastral Surveyor under Group #736, surveyed May/June 1971 (DCSO records Vol. 37 Page(s) 15355)

-----  
Point for the NW 1/16 sec. cor. of sec. 7, at intersection with the E. & W. center line of the NW ¼ of sec. 7.

Set an iron post, 28" long, 2¼" dia, 22" in the ground, and in a mound of stone, 3' base, to top, with brass cap mkd:

NW 1/16 S 7  
1971

from which a bearing tree mkd: by Stewart in 1922

An ash, 21" dia., bears S.41°W., 30 lks., with scribe marks 1/16 BT visible on partially healed blaze.

and a bearing tree mkd. by Ramsey in 1967

A cedar, 18" dia., bears S.27°E., 40 lks., with scribe marks NW 1/16 S& RS404 BT visible on partially healed blaze.

and a new bearing tree

A fir, 16" dia., bears N.48½°W., 145 lks., mkd: NW 1/16 S7 BT.

From this point, a point established and recorded by G.G. Stewart, Deputy County Surveyor, in 1922, subsequently remonumented by Marvin C. Ramsey, Registered Land Surveyor No. 404, in 1967, with an iron pipe, 1" dia., protruding 4" above the ground, firmly set, bears N.71°E., 0.295 chs.