TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 120600

PRIMARY CORNER DESCRIPTION W 1/16 Secs. 6 & 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

---

BLM resurvey by Larry Evans, Cadastral Surveyor under Group #736, surveyed May/June 1971 (DCSO records Vol. 37 Pg 15342)

---

Point for the W 1/16 sec. cor. of secs. 6 & 7.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

W 1/16 $\frac{S\ 6}{S\ 7}$
1971

from which
A W.Fir, 8" dia., bears N.3°W., 14 lks., mkd: W 1/16 S6 BT
A Fir, 12" dia., bears S.8°E., 24 lks., mkd: W 1/16 S7 BT.

---

Douglas Co. Surveyors Office - Stephen J. Flause - Kody Inda - 12/13/2007 - C.S. File 67/25-1

---

Found - 3.25" dia. brass cap (properly mkd) on a 2.5" O.D. iron pipe firmly set & protruding approx. 6" above ground.
Evidence of two orig. BTs fd.
A W.Fir, 8" dia., now a shattered & rotted 1½ ft. tall fir stump of interminable dia. with a properly scribed single blaze face still intact, bears N.3°W., 9.2 ft. (as per rec.)
A Fir 12" dia., now a 22" DBH D.Fir with a fully healed single blaze bears S.8°E., 15.8 ft. (as per rec.)
New - A 15" dia., D.Fir scribed "W 1/16 S6 CS BT" on a double blaze bears N.4½°E., 18.0 ft.
Note - Corner is on moderate NE slope near bottom of steep NE running ridge. Cor. is also approx. 300 ft. north of NE-SW switch-back in graveled forest access rd.
Compass decl. 16¼°E.

---

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 1/2017 - C.S. File 65/95-2

---

Found - 3¼" brass cap (properly mkd)
Root hole N.3°W., 9.2 ft. (per rec.)
23" Fir, rec. 22", S.8°E., 15.8 ft. healed blaze.
16" Fir N.4½°E., 18.0 ft., vis scribe.
Note - Compass decl. 15½°E.
Corner on east slope approx 350' east of road.

---

Fd. Ok by D Baker - 7/2019 - M176-18