

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 30 only

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8538)

Set a Fir post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. corner, marked ¼ S on N. face; from which
 A Fir 36" dia., bears N.11°E., 132 lks. mkd. ¼ S BT.
 A Fir 20" dia., bears S.52°W., 88 lks. mkd. ¼ S BT.
 This corner is on the E. slope of spur, 100 ft. above ravine.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, W. Penley, crew - May 11, 1970 - C.S. File 54/114-18

Found - 36" now 52" D.Fir N.11°E., 87.1 ft., opened for scribed "S"
 No trace of other BT. (S.52°W)
 Set Brass cap at cor. mkd: County Surveyors Office
 T 32 S R 4 W
 ¼ S 19
 S 30
 1970
 New BTs -10" D.Fir N.6°W., 11.5 ft. mkd. ¼ S19 CS BT.
 8" D.Fir S.71°W., 6.2 ft. mkd. ¼ S30 CS BT.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #977 Surveyed, May/June 1979 - (DCSO records Vol. 43 Page(s) 16773-74)

The ¼ sec. cor. of sec. 30 only, perpetuated and recorded by Powell in 1970, monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T32S R4W 1/4 S19|S30 1970, from which the remains of the original bearing trees:
 A Fir 57" dia., bears N.11°E., 132 lks. dist., with illegible scribe marks visible on opened blaze.
 A roothole bears S.52°W., 88 lks. dist.
 and bearing trees mkd. by Powell:
 A Fir 14" dia., bears N.6°W., 17 lks. dist., with healed double blaze.
 A Fir 8" dia., bears S.69°W., 9½ lks. dist., with healed blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

 1/4 S 30
 T 32 S R 4 W
 1979

(Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 30 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which a new bearing tree
A Fir 16" dia., bears S.4½°E., 18 lks. dist., mkd. ¼ S30
BT.
Invert and reset iron pipe alongside the iron post.