

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by James Artman, L.S. #2268 - For: Medford Corp. -  
March 16, 1990 - C.S. File 63/101 and M 109-66

-----  
Set 5/8" x 30" Iron rod with cap mkd. "Artman RLS 1168".  
New BTs -10" Chinquapin bears S.51°30'E., 2.1 ft. scribed "C  
¼ S18 BT"  
5" Chinquapin bears N.3°30'E., 10.7 ft. scribed "C  
¼ S18 BT"  
14" D.Fir bears S.67°30'E., 10.7 ft. scribed "C ¼  
S18 BT."  
5" D.Fir bears N.59°E., 23.2 ft. scribed "C ¼ S18  
BT"

Fd. I.R., R. Brown, July 1993, M 117-58

Found OK by R. Wytcherley, April 2003 See M142-35

Kristian DeGroot - For: Silver Butte Timber Co. - 10/2010 -  
M157-32

-----  
LAT: 42°47'24.199163" N. LONG: 123°13'05.645145" W.  
Set a 5/8"x30" iron rod, 24" in the ground, with a 2"  
aluminum cap stamped:

T32S R4W  
C ¼  
•  
S 18  
2010  
PLS 1941

From which the BTs mkd by Artman per M 106-66 with new ties:  
A 4" D.Fir snag bears N.55°15'E., 21.9 ft. with scribe  
marks "X" and "BT" visible  
A 20" d.fir bears S.69°E., 8.3 ft. with healed double  
blaze  
A 10" Chinquapin stump bears S.87°30'W., 3.6 ft  
And a new bearing tree:  
A 21" D.Fir bears N.32°15'E., 32.9 ft scribed "C ¼ S18 BT"  
And a new reference monument:  
A 5/8"x30" iron rod bears S.28°23'16"W., 14.08 ft.  
And a monument by Artman per M109-66:  
A 5/8" IR bears N.65°55'13"W. 2.25 ft this corner was  
errantly set by improper boundary control procedures,  
and therefore rejected. I drive rod 3" below ground.

Fd 5/8" IR, bent by logging operation and 2 Fir BTS, now  
stumps with BT tag on top - 2/2020 by R Brown - M176-60