

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8462)

Set ¼ sec. post, from which
A B.Oak 6" dia., bears N.40°E., 24 lks. dist.
A Pine 7" dia., bears S.30°W., 29 lks. dist.

G.G. Stewart, Deputy Co. Surveyor - May 1922 - Vol. 3 Page 121 and M 3-32 and C.S. File 45/186

Set stake with brick for corner. Found two original BTs.
Marked - An 18" Pine S.27°W., 20.0 ft. (O.B.T.)
An 18" Pine N.43°E., 45.6 ft.

George J. Wenderoth, L.S. #5 - August 6, 1944 - C.S. File 39/158 and 39/159

Set ½" x 36" Iron pipe.
Found stump of old bearing tree scribed. Other tree scribe marks burned off.
Marked two new bearing trees:
12" Fir N.89°52'E., 39.8 ft.
24" Pine S.23°17'E., 21.0 ft.

George J. Wenderoth - For: J. Fowler - May 1965 - C.S. File 54/5

Found - Stump of Fir BT, N.89°52'E., 39.8 ft. scribed.
Stump of Pine S.23°17'E., 21 ft., cut years ago.
¾" Iron pipe, badly bent from logging.
Set brass cap at corner, from which
10" Fir N.43°25'W., 31.2 ft.
24" Fir S.1°E., 40.1 ft.

Cor. Fd. and used in BLM survey by Larry Evans, under Group #736, surveyed May/June 1971 (DCSO records, Vol. 37 Page 15337)

Found OK by R. Wytcherley, April 2003 See M142-35

FD. BC & accessories by K.DeGroot, 10/2010 - M157-32
LAT: 42°47'50.015437" N. LONG: 123°13'05.686480" W.