

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 140540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 7

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

G.G. Stewart, Deputy Co. Surveyor - May 1922 - Vol. 3 Pg. 121 and M 3-32 and C.S. File 45/186

Set an iron pipe at intersection of center lines of section.
Marked - 36" Fir S.7°E., 64.0 ft.
6" Fir S.40°W., 62.0 ft.

Gerald Riley - For: Angus Cripps - Aug. 1967 - C.S. File 55/57 A & B

Not found - destroyed by logging.

BLM resurvey by Larry Evans, Cadastral Surveyor under Group #736, surveyed May/June 1971 (DCSO records Vol. 37 Page(s) 15351)

Point for the center ¼ sec. cor. of sec. 7, at intersection with the E. and W. center line of sec. 7.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: C 1/4 S 7
1971

from which

A Fir 13" dia., bears S.67°E., 148½ lks. dist., mkd. C ¼ S7 BT.

A Fir 12" dia., bears S.42°W., 155 lks. dist., mkd. C ¼ S7 BT.

Fd. BC by Neil Hibbs, 7/2009 - 2009-0043

Fd. BC by Neil Hibbs, 7/2013 - M165-46