

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8533-34)

Set a Madrona post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. corner, marked ¼ S on W. face; from which
A dead Fir 24" dia., bears N.32½°W., 16 lks. mkd. ¼ S BT.
A Fir 12" dia., bears N.62°E., 62 lks. mkd. ¼ S BT.
This corner is on NE. slope of spur, 200 ft. above creek.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, W. Penley, crew - May 22, 1970 - C.S. File 54/114-39

Found - Unrecorded 1" Iron pipe for corner, S.62°W., 2.0 ft.
12" now 28" D.Fir N.62°E., 40.9 ft., tree opened earlier for scribe "¼" and other pitched over scribe marks.
24" dead Fir now down and burnt, N.31½°W., 10.6 ft.
Set Brass cap at cor. mkd: County Surveyors Office
T 32 S R 4 W
¼ S 32 | S 33
1970
New BTs -22" D.Fir S.30°E., 24.1 ft. mkd. ¼ S32 CS BT.
6" Laurel N.32°W., 20.3 ft. mkd. ¼ S31 CS BT.