

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8473-74)

-----  
 Set a Madrona post 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 29, 30, 31 and 32, mkd. T32S S29 on NE.; R4W S32 on SE.; S31 on SW.; and S30 on NW.; faces with 1 notch on W. and 5 notches on E. faces, from which  
     A Fir 40" dia., bears N.15°E., 49 lks. mkd. T32S R4W S29 BT.  
     A Madrona 6" dia., bears S.51°E., 49 lks. mkd. T32S R4W S32 bT.B  
     A Fir 10" dia., bears S.26½°W., 115 lks. dist., mkd. T32S R4W S31 BT.  
     A Fir 24" dia., bears N.68½°W., 76 lks. dist. mkd. T32S R4W S30 BT.  
 This cor. is on a hillside, sloping W., 100 ft. below top of ridge.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, W. Penley, crew - May 20, 1970 - C.S. File 54/114-42

-----  
 Found - 40" now 48" D.Fir N.15°E., 32.3 ft. shows good scar.  
           10" now 22" D.Fir S.26½°W., 75.9 ft. shows good scar  
           24" D.Fir now stump N.68¼°W., 50.2 ft. opened for scribe.  
           No trace of SE Laurel BT.  
 Set Brass cap at cor. mkd:           County Surveyors Office  
   T 32 S R 4 W  
   S 30 | S 29  
   S 31 | S 32  
   1970  
 New BTs -13" Y.Pine N.74°W., 24.1 ft. mkd. T32S R4W S30 CSBT  
           6" D.Fir S.40°E., 24.4 ft. mkd. T32S R4W S32 CS BT.  
 This cor. lies on S. slope about 450.0 ft. South of ridge top, good N-S blazed line.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #977 Surveyed, May/June 1979 - (DCSO records Vol. 43 Page(s) 16768)

-----  
 The Sec. cor., perpetuated and recorded by Powell in 1970, monumented with an iron pipe 1¼" dia., firmly set, projecting 12" above the ground with 1970 brass cap.  
 from which the remains of the original bearing trees  
     A Fir 54" dia., bears N.15°E., 49 lks. with healed blaze.  
     A Fir 29" dia., bears S.26½°W., 111 lks. with healed blaze. (Rec. 115 lks.)                   (Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed Fir stump 37" dia., bears N.68½°W., 76 lks. dist., with scribe marks 2S W visible on opened and burned blaze.  
and bearing trees mkd. by Powell  
A Fir snag 7" dia., bears S.42°E., 37 lks. with scribe marks T32S R4W S32 CS BT visible on partially healed blaze.  
A Sugar Pine 17" dia., bears N.74¼°W., 36½ lks. dist., with scribe marks 4W CS B visible on partially healed blaze.  
and a new bearing tree  
A Fir 20" dia., bears S.88°E., 76½ lks. dist., mkd. T32S R4W S32 BT.