

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8535-36)

Set a Madrona post, 3 ft. long, 4" sq., 24" in the ground for a corner of secs. 19, 20, 29 and 30, marked T32S S20 on NE.; R4W S29 on SE.; S30 on SW.; and S19 on NW. faces, with 2 notches on S. and 5 notches on E. edges; from which
A Fir 24" dia., bears N.97½°E., 300 lks. dist., marked T32S R4W S20 BT.
A Fir 20" dia., bears S.6°E., 120 lks. dist., marked T32S R4W S29 BT.
A Fir 8" dia., bears S.14°W., 141 lks. dist., marked T32S R4W S30 BT.
A Cedar 20" dia., bears N.58°W., 105 lks. dist., marked T32S R4W S19 BT.
This corner is on the S. slope of spur, 150 ft. above creek.

George J. Wenderoth, Deputy Co. Surveyor - April 14, 1947 - C.S. File 38/246-1

Found 3 old BTs:
36" Fir bearing S.6°E., 79.2 ft.
20" Fir bearing S.14°W., 93.0ft.
30" Cedar bearing N.58°W., 69.3 ft., down.
Set 1¼" I.Pipe for the corner, and marked BTs:
4" Fir bearing N.11°55'E., 28.1 ft.
4" Pine bearing N.83°02'W., 34.1 ft.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #977 Surveyed, May/June 1979 - (DCSO records Vol. 43 Page(s) 16772)

The Sec. cor., perpetuated and recorded by Wenderoth in 1948, monumented with an iron pipe, 1½" dia., firmly set, projectig 10" above ground, from which the remains of the original bearing trees:
A Fir 52' dia., bears S.6°E., 122 lks. dist., with illegible scribe marks visible on opened blaze. (Rec. 120 lks.)
A Fir 36" dia., bears S.14°W., 138½ lks. dist., with healed blaze. (Rec. 141 lks.)
A rotted Cedar stump, 30" dia., bears N.58°W., 105 lks. dist., alongside of which is lying a burned and rotted Cedar, no marks visible.
and bearing trees mkd. by Wenderoth:
A Fir 10" dia., bears N.12 3/4°E., 43 lks. dist., with healed blaze. (Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Knobcone Pine 7" dia., bears N.82°W., 53 lks. dist.,
with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground,
directly over the iron pipe, with brass cap mkd:

T 32 S R 4 W

S 19 S 20

S 30 S 29

1979

from which a new bearing tree

A Fir 6" dia., bears N.37½°W., 29 lks. dist., mkd. T32S
R4W S19 BT.

Fd. Ok by Kris DeGroot - 1/2005 - M 146-16

Fd. Per record by R Quimby, 7/2019 - M175-78 A-B