

PRIMARY CORNER DESCRIPTION West 1/4 Cor. 20 only

Alias	Description

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8540)

-----  
Set a Fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. corner, marked ¼ S on W. face; from which  
A Fir 18" dia., bears S.50°E., 5 lks. mkd. ¼ S BT.  
A Fir 16" dia., bears S.23°W., 14 lks. mkd. ¼ S BT.  
This corner is on N. slope of spur, 250 ft. below top.

George J. Wenderoth, Deputy Co. Surveyor - May 1947 - C.S. File 38/246-1

-----  
Found Both BTs in good shape.  
Drove 1½" I.Pipe and marked the following BTs:  
30" Fir bearing S.50°E., 2.2 ft.  
30" Fir bearing S.23°W., 6.1 ft.

Kris DeGroot - For: Silver Butte Timber - 1/2005 - M 146-16

-----  
Found - 2¼" (O.D.) iron pipe projecting 12" above the ground per CS 38/246-1  
New - A 19" D.Fir bears S.33°00'E., 14.4 ft scribed "¼ S20 BT"  
A 8" D.Fir bears N.55°00'W., 26.8 ft scribed "¼ S19 BT"  
A 5/8" iron rod bears N.33°00'W., 15.00 ft.  
A 5/8" iron rod bears S.56°00'E., 20.00 ft.