

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8542)

At point of intersection, I set a Cedar post 3 ft. long 4" sq., 24" in the ground for a closing corner of secs. 17 and 20, marked C C T32S R4W on E.; S17 on N.; and S20 on S. faces, with 5 grooves on E. and 3 grooves on S. faces; from which

A Fir 24" dia., bears N.38°E., 46 lks. dist., mkd. T32S R4W S17 BT.

A Fir 26" dia., bears S.27°E., 85 lks. dist., mkd. T32S R4W S20 BT.

This corner is on a NE. slope, 75 ft. above creek bottom.

George J. Wenderoth, Deputy Co. Surveyor - Wit: Clifford Worley - Oct. 1946 - C.S. File 39/158

Found stumps of both old BTs.

Drive 3/4" pipe for corner.

Scribe - 5" Chinquapin N.87°25'E., 53.5 ft.

8" Chinquapin S.21°47'E., 78.8 ft.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, W. Penley, crew - May 8, 1970 - C.S. File 54/114-16

Found - Orig. 24" D.Fir, stump, N.38°E., 30.4 ft., has burnt face.

Orig. 26" D.Fir, stump, S.27°E., 56.1 ft., opened for scribe "B"

1" Iron pipe set by Wenderoth which bears S.4°W., 10.7 ft.

5" Chinquapin, dead, N.77½°E., 53.5 ft. (Rec. N.87½°E.) rotted scribe visible.

8" Chinquapin, dead, S.11°E., 13.8 ft. (Rec. S.22°E., 78.8 ft.) rotted scribe visible.

Set Brass cap at closing cor. mkd: County Surveyors Office

T 32 S R 4 W

CC S 18 | S 17
 | S 20

1970

New BTs -11" Cedar N.71°E., 11.9 ft. mkd. T32S R4W S12 CC CS BT.

9" D.Fir S.50°E., 16.7 ft. mkd: T32S R4W S20 CC CS BT.

6" D.Fir S.44°W., 13.9 ft. mkd: S18 CS BT.

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 200411

PRIMARY CORNER DESCRIPTION CC Secs. 17 & 20 only. (E. bdy. Sec. 18)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Chinquapin snag 8" dia., bears N.77½°E., 83½ lks. dit.,
no marks visible on decayed blaze.

A Chinquapin stump 5" dia., bears S.11°E., 20½ lks. dist.,
with illegible scribe marks visible on decayed blaze.

A Chinquapin snag 7" dia., bears S.59°W., 36½ lks. dist.,
with scribe marks CS BT visible on partially healed
blaze.

Fd. OK, James Artman, March 1990, M 109-66

Fd. BC, Raymond Brown, 10/2012 - M164-41

Fd BC, 2/2020 by R Brown - M176-60