

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 18 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8462)

-----  
Set ¼ sec. post, from which  
A Fir 30" dia., bears S.60°E., 9 lks. dist.  
A Cedar 8" dia., bears S.70°W., 40 lks. dist.

George J. Wenderoth, Deputy Co. Surveyor - 1947-48 - C.S. File 38/246

-----  
Set 1" Iron pipe halfway bet sec. cors.  
20" Fir bearing S.15°19'W., 41.5 ft.  
30" Fir bearing N.51°50'W., 32.5 ft.

George J. Wenderoth, Deputy - June 18, 1960 - C.S. 52/29-3

-----  
Found - Stumps of both witness trees as renewed before and 1" Iron pipe.  
Put in new trees as follows:  
10" Fir N.12°49'W., 69.1 ft.  
24" Cedar S.48°16'W., 155.1 ft.

BLM resurvey by Larry Evans, Cadastral Surveyor under Group #736, surveyed May/June 1971 (DCSO records Vol. 37 Page(s) 15334)

-----  
Point for the ¼ sec. cor. of secs. 18 only, at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.

From this point, a point established and recorded by Wenderoth in 1946, bears S.50°W., 0.095 chs. dist., monumented with an iron pipe 1" dia., protruding 6" above ground, firmly set, from which bearing trees mkd. by Wenderoth:

A sawed Fir stump 18" dia., bears S.16°W., 63 lks. dist., with scribe marks BT visible on open blaze.  
A sawed Fir stump 41" dia., bears N.46½°W., 58 lks. dist., with illegible scribe marks visible on open blaze.  
and bearing trees mkd. by Wenderoth in 1960  
A Cedar 24" dia., bears S.45½°W., 232½ lks. dist., with scribe marks ¼ S18 visible on partially healed double blaze.  
A Fir 11" dia., bears N.15 ¾°W., 105 lks. dist., mkd. with a healed double blaze.

continued next page

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 18 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Fd. Wenderoth's 1" I.P.- J. Artman, March 16, 1990, M 109-66

Found OK by R. Wytcherley, April 2003 See M142-35

Kristian DeGroot - For: Silver Butte Timber Co. - 10/2010 - M157-32

-----  
LAT: 42°47'25.266473"N. LONG: 123°12'29.763449" W.  
Set a 5/8"x30" iron rod, 24" in the ground, with a 2" aluminum cap stamped:

1/4  
T32S R4W  
S18 • ONLY  
2010  
PLS 1941

From which the remains of BTs marked by Wenderoth in 1948 with new ties:

A 18" rotted Fir stump bears S.19°15'W., 47.2 ft. with partially rotted face.

A 41" rotted Fir stump bears N.59°15'W., 39.8 ft. with illegible scribe mks visible

And the BT marked by Wenderoth in 1960 with new ties:

A 28" Cedar bears S.43°45'W., 161.2 ft. with fully healed double blaze

A 18" D.Fir bears N.23°45'W., 67.0 ft. with fully healed double blaze

And new bearing trees:

A 10" D.Fir bears S.85°15'W.. 9.8 ft. scribed "1/4 S18 BT"

A 12" D.Fir bears N.17°W., 11.6 ft., scribed "1/4 S18 BT"

And a monument by Wenderoth per CS 38/246

A 1" iron pipe bears S.54°48'21"W., 6.99 ft. (rec. S.50°W., 0.095 chs.)

BLM Dependent resurvey by Ernest Q. Lundeen, Cadastral Surveyor, under Group No. 2790, surveyed July 2015 - (DCSO records Vol. 58 Page(s) 23438-9)

-----  
The 1/4 sec. cor. of sec. 18 only, reestablished by DeGroot, in 2010, at record latitudinal distance, per Evans' 1971 resurvey, from the cor. established by Wendroth, PLS No. 5, in 1946, and on line between the 1/4 sec. cor. and the S. 1/16 sec. cor. of sec. 17 only, on the E. bdy. of sec. 18, as resurveyed by DeGroot. There is no remaining evidence of the original cor. and this position is accepted as the cor.; monumented with an iron rod, 5/8" dia., firmly set, projecting 5" above the ground, with an aluminum cap, 2" dia., (properly) mkd.

continued next page

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 18 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which bearing trees mkd. by DeGroot  
A fir, 10" dia., bears S.88½°W., 9.8 ft., with illegible scribe marks visible on partially healed upper blaze and scribe mark T visible on partially healed lower blaze.  
A fir, 12" dia., bears N.14¼°W., 11.6 ft., with illegible scribe marks visible on partially healed upper and lower blazes.  
From this cor., a point established by Wendroth, in 1946, and perpetuated by Wendroth, in 1960, under C.S. File No. 52/29, bears S. 50° W., 6.96 ft., this point was used by DeGroot to reestablish the ¼ sec. cor. of sec. 18 only; monumented with an iron pipe, 1" dia., firmly set, projecting 6" above the ground, from which bearing trees mkd. by Wendroth in 1946.  
A rotted sawed fir stump, 30" dia., bears S.16°W., 41.6 ft., with illegible scribe marks visible on rotted opened blaze.  
A rotted sawed fir stump, 40" dia., bears N.46½°W., 38.3 ft., with scribe marks S 8 CS visible on exposed blaze. and bearing trees mkd. by Wendroth in 1960  
A cedar, 39" dia., bears S.45½°W., 153.5 ft., with a healed blaze.  
A fir, 18" dia., bears N.15¼°W., 69.3 ft., with a healed double blaze.

Fd 5/8" IR per M157-32 - 2/2020 by R Brown - M176-60