

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 17 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

George J. Wenderoth, Deputy Co. Surveyor - 1946 - C.S. File 44/119

Set 1" I. Pipe halfway between corners, scribed following BTs
8" Chinquapin bearing S.43°32'E., 12.3 ft.
30" Fir bearing N.39°00'E., 12.4 ft.

Douglas Co. Surveyors Office, John Powell, deputy - May 6, 1970 - C.S. File 54/114-14

Found - 8" Chinquapin now 13" S.43½°E., 12.3 ft. scribe marks visible.
30" now 33" D.Fir N.69°E., 12.4 ft., tree opened and face painted.
1" Iron pipe at ¼ corner.
Unrecorded 3/4" Iron pipe, South 9.7 ft. from corner
9" Laurel N.62½°W., 10.6 ft. from corner.
Trees for Section 17 tagged.

BLM resurvey by Larry Evans, Cadastral Surveyor under Group #736, surveyed May/June 1971 (DCSO records Vol. 37 Page(s) 15335)

Point for the ¼ sec. cor. of sec. 17 only, at midpoint latitudinally on the W. bdy. of sec. 17.
Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd:
T 32 S R 4 W
| 1/4 S 17
1971

from which bearing trees mkd. by Wenderoth in 1946:
A Fir 32" dia., bears N.25 3/4°E., 13½ lks. dist., with healed blaze.
A Chinquapin 11" dia., bears S.20°E., 18 lks. dist., with scribe marks 4S S17 BT visible on partially healed blaze.

From this point, a point established and recorded by Wenderoth in 1946, bears S.64°W., 0.075 chs. dist., monumented with an iron pipe 1" dia., protruding 6" above ground, firmly set.

From this same point, another point established and recorded by Wenderoth in 1946, bears S.22°W., 0.095 chs. dist., monumented with an iron pipe 3/4" dia., protruding 6" above ground, firmly set, from which bearing trees mkd. by Wenderoth in 1946:

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 17 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Chinquapin 6" dia., bears S.47½°W., 6 lks. dist., with scribe mark S visible on partially healed blaze.
A Madrone 8" dia., bears N.32°W., 25½ lks. dist., with scribe marks CS BT visible on partially healed blaze.

Kristian DeGroot - For: Silver Butte Timber Co. - 10/2010 - M157-32

LAT: 42°47'31.894928" N. LONG: 123°12'29.859212" W.
Fd a 1971 USBLM iron post by Evans, firmly set, projecting 6" above the ground, with a properly marked 3¼" brass cap:
From which the BTs marked by Wenderoth in 1946:
A 41" D.Fir bears N.25°45'E., 8,9 ft, with a healed blaze.
A 17" chinquapin bears S.20°E., 11.9 ft. with a healed blaze.
And monuments established by Wenderoth:
A 1" iron pipe bears S.65°22'11"W., 4.88 ft (rec. S.64°W., 0.075 chs.)
A ¾" iron pipe bears S.22°28'54"W., 12.77 ft (rec. S.22°W. 0.095 chs.)

BLM Dependent resurvey by Ernest Q. Lundeen, Cadastral Surveyor, under Group No. 2790, surveyed July 2015 - (DCSO records Vol. 58 Page(s) 23438-9)

The ¼ cor. of sec. 17 only, monumented with an iron post, 2½" dia., firmly set, projecting 4" above the ground, with brass cap (properly) mkd.
from which bearing trees mkd. by Wendroth, PLS No. 5, in 1946
A fir, 43" dia., bears N.25¾°E., 8.9 ft., with a healed blaze.
A chinquapin, 17" dia., bears S.20°E., 11.9 ft., with a healed blaze.
From this cor., a point established by Wendroth, in 1946, bears S.64°W., 4.95 ft.; monumented with an iron pipe, 1" dia., firmly set, projecting 6" above the ground.
From this same cor., another point established by Wendroth, in 1946, bears S.22°W., 12.87 ft.; monumented with an iron pipe, ¾" dia., firmly set, projecting 6" above the ground, from which bearing trees mkd. by Wendroth.
A chinquapin, 7" dia., bears S.44½°W., 4.7 ft., with illegible scribe marks visible on partially healed upper and lower blazes. (Record, S.47½°W., 4.0 ft.)
A madrone 9" dia., bears N.32°W., 16.8 ft., with illegible scribe marks visible on partially healed upper and lower blazes.