

PRIMARY CORNER DESCRIPTION C C for Secs. 8 & 17 on E. bdy Sec. 7

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8544)

At point of intersection,
I set a Fir post 3 ft. long, 4" sq., 24" in the ground for a closing corner of secs. 8 and 17, mkd. CC T32S R4W on E.; S8 on N.; and S17 on S. faces, with 4 grooves on S. and 5 grooves on E. faces, from which

A Madrona 12" dia., bears S.52°E., 38 lks. mkd. T32S R4W S17 BT.

A Madrona 16" dia., bears N.75°E., 27 lks. mkd. T32S R4W S8 BT.

This corner is on NW. slope of spur, 25 ft. below top.

George J. Wenderoth, Deputy Co. Surveyor - 1946 - C.S. File 44/119

Found both old BTs badly decayed.

Drove 1" I.Pipe for the corner, from which
12" Madrona bearing S.52°E., 25.0 ft.
16" Madrona bearing N.75°E., 17.8 ft.

New BTs - 30" Fir bearing N.75°48'E., 36.0 ft.
30" Fir bearing S.35°05'E., 29.0 ft.

BLM resurvey by Larry Evans, Cadastral Surveyor under Group #736, surveyed May/June 1971 (DCSO records Vol. 37 Page(s) 15350)

(27.365 chs.)

The original closing cor. of secs. 8 and 17, perpetuated and recorded by Wenderoth in 1946, monumented with an iron pipe 1" dia., protruding 1" above ground, firmly set, from which the remains of the original 1897 bearing trees:

A Madrone 25" dia., bears N.75°E., 27 lks. with scribe marks S8 visible on partially opened blaze.

A Madrone snag 15" dia., bears S.52°E., 38 lks. dist., with scribe marks R4W S17 visible on partially opened blaze.

and bearing trees mkd. by Wenderoth

A Fir 32" dia., bears N.75 3/4°E., 56 lks. with healed blaze.

A Fir 33" dia., bears S.35¼°E., 45½ lks. dist. with healed blaze.

(S.89°22'W.,) (27.65)

Intersect the E. bdy. of sec. 7
(Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 200509

PRIMARY CORNER DESCRIPTION CC for 8 & 17 only, on E. bdy. Sec. 7

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

True point for the closing cor. of secs. 8 and 17.
Set an iron post, 28" long 2½" dia., 24" in the ground with
brass cap mkd:

T 32 S R 4 W

S 7 $\frac{S 8}{S 17}$ CC

1971

from which bearing trees mkd. by Wenderoth

A Fir 32" dia., bears N.79½°E., 83½ lks. with healed blaze

A Fir 33" dia., bears S.57°E., 66 lks. with healed blaze.

(From this point, the cor. of secs. 7 and 18 only, on the W.
bdy. of sec. 17, bears S.1°06'E., 10.105 chs. dist.)

Fd. OK, April 1991, M 113-10