

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8473)

Set a Fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. corner, mkd. ¼ S on N. face; from which
A Fir 30" dia., bears N.9°E., 145 lks. mkd. ¼ S BT.
A Fir 24" dia., bears S.13½°E., 132 lks. mkd. ¼ S BT.
This cor. is on a hillside sloping SE., 25 ft. above ravine

George J. Wenderoth - 1947-48 - (No record source found, information from previous renewal records, #20)

Found the stumps of the old BTs:
40" Fir bearing N.9°E., 95.7 ft.
30" Fir bearing S.13½°E., 87.1 ft.
Set 1" I.Pipe for the corner and mkd. the following BTs
30" Fir bearing S.22°20'E., 129.9 ft.
24" Fir bearing N.19°48'E., 98.7 ft.

Fd. OK, DCSO, J.Powell, May 5, 1970, C.S. File 54/114-11

Fd 1" IP 4/1990 (added 7/29/2019)by J. Artman M110-11

Ron Quimby For: Silver Butte Tbr Co. - July 2019 - M175-78A-B

Found - 1" iron pipe 6" above ground
4' tall rotten stump bears N.9°E., 95.7'
2' tall rotten stump bears S.13½°E., 87.1'
34" Fir bears S.22°20'E., 129.9'
30" Fir bears N.19°48'E., 98.7'
T-Post bears 1.5' West
New BTs- 13" Fir bears N.02°W., 15.6' scribed "¼ S29BT"
12" Fir bears S.24°W., 28.4' scribed "¼ S32BT"