

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8537)

-----  
Set a Yew post, 3 ft. long, 4" sq., 24" in the ground, marked ¼ S on N. face, for ¼ sec. corner, from which  
A Fir 30" dia., bears S.47°W., 69 lks. mkd. ¼ S BT.  
A Fir 20" dia., bears N.20°W., 181 lks. mkd. ¼ S BT.  
From this corner, the NW. corner of Starvout Post Office bears N.57°E., 264 lks. dist.

George J. Wenderoth, Deputy Co. Surveyor - April 14, 1947 - C.S. File 38/246-1

-----  
Set 1" I.Pipe for the corner between (halfway) sec. cors.  
12" Fir bearing N.50°E., 32.4 ft.  
10" Alder bearing S.7°23'E., 31.6 ft.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12800)

-----  
The ¼ sec. cor., determined at record bearing and distance from the remaining original bearing tree:  
A Fir snag 36" dia., bears S.47°W., 69 lks. dist., marked with an opened blaze.  
At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, and in a mound of stone, to top, with brass cap mkd:  
¼  $\frac{S\ 20}{S\ 29}$   
T32S R4W  
1959  
from which new bearing trees  
A Fir 13" dia., bears N.51°E., 49 lks. mkd. ¼ S20 BT.  
A Fir 10" dia., bears S.18°W., 12 lks. mkd. ¼ S29 BT.

Kris DeGroot - For: Silver Butte Timber - 1/2005 - M 146-16

-----  
Found - 2½" (O.D.) iron pipe by USBLM Cadastral surveyor Thielsen in 1959, firmly set projecting 8" above the ground with a 3¼" USBLM standard brass cap (properly) stamped.  
From which a BT by Wenderoth in 1947 per CS 38/246-1 A 36" D.Fir bears N.50°E., 33.4 ft. with a healed blaze (Rec. N.50°E., 32.4 ft.)

continued next page

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

And a BT by Thielsen in 1959  
A 30" D.Fir bears S.16°45'W., 7.4 ft. (Rec. S.18°E.,  
12 lks.  
New - A 8" D.Fir bears N.45°15'W, 26.8 ft scribed "¼ S20  
BT"  
A 19" D.Fir bears S.73°15'E, 19.2 ft scribed "¼ S29  
BT"  
A 5/8" iron rod set 26" in the ground W/PC marked  
"BTS ENG-SURV" bears S.17°58'18"W, 16.54 ft

---

Ron Quimby For: Silver Butte Tbr Co. - July 2019 - M175-78A-B  
-----  
Found - Brass cap per M146-16 RECORDS OF DOUGLAS COUNTY  
38" stump bears N.16°45'W 7.4'  
9" Fir bears N.45°15'W., 26.8' with visible blaze  
24" Fir bears S.73°15'E., 19.2' with visible blaze  
5/8" iron rod bears S.17°58'18"W., 16.54'