

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8541)

 Set a Fir post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. corner, marked ¼ S on N. face; from which
 A Fir 24" dia., bears S.36°E., 149 lks. mkd. ¼ S BT.
 A Madrona 8" dia., bears N.78°W., 21 lks. mkd. ¼ S BT.

George J. Wenderoth, Deputy Co. Surveyor - (1940's) C.S. File 44/119

 Found an old BT and rescribe.
 Drive 3/4" Pipe for corner, from which
 28" Madrone bears N.79°47'W., 13.3 ft. (old BT)
 10" Fir bears S.47°08'W., 47.8 ft. (new BT)

Fd. OK, DCSO, J.Powell, May 1970, C.S. File 54/114-10

BLM resurvey by Larry Evans, Cadastral Surveyor under Group #736, surveyed May/June 1971 (DCSO records Vol. 37 Page(s) 15343-44)

 The ¼ sec. cor. perpetuated and recorded by Wenderoth in 1946, monumented with an iron pipe 3/4" dia., protruding 8" above the ground, firmly set, at record bearing and distance from the remaining original 1897 bearing tree:

 A Madrone 28" dia., bears N.78°W., 21 lks. with healed blaze. (Rescribed by Wenderoth in 1946)
 and a bearing tree mkd. by Wenderoth
 A Fir 16" dia., bears S.46°W., 72½ lks. dist., mkd. with healed double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground directly over the iron pipe, with brass cap mkd:

T 32 S R 4 W
 ¼ S 17
 S 20
 1971

from which a new bearing tree

 A Fir 8" dia., bears N.28 3/4°E., 72 lks. mkd. ¼ S17 BT.

Douglas Co. Surveyors Office, Gregory Quibell, Deputy - John Powell, Randy Smith, crew - Dec. 20, 1982 - C.S. 62/1-37

 Found - 2½" I.P. with 1971 BLM brass cap attached, firmly set 0.4 ft. North of fence corner.

(Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Orig. 8" now 28" Madrone, bark gone, blaze not visible, bears N.78°W., 13.8 ft. Tree is dead and soon to be cut down. I move BT tags to base of tree.
10" now 19" Fir with good double blaze bears S.46°W., 47.8 ft.
8" now 13" Fir, with good single blaze bears N.28 3/4°E., 47.5 ft.
New BT - 11" Cedar scribed "¼ S17 CS BT" in double blaze bears N.76°E., 64.6 ft.
Douglas Co. Surveyors Office BT tags on all trees.

Fd. ok by Kris DeGroot- 1/2005 - M 146-16