

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8471-72)

-----  
Set a Yew post 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 28, 33, 32 and 29, mkd. T32S S28 on NE.; R4W S33 on SE.; S32 on SW.; and S29 on NW. faces, with 4 notches on E. and 2 notches on W. edges, from which

A Fir 40" dia., bears N.66°E., 69 lks. dist., mkd. T32S R4W S28 BT.

A dead Fir 30" dia., bears S.34°E., 64 lks. dist., mkd. T32S R4W S33 BT.

A dead Fir 36" dia., bears S.13°W., 21 lks. dist., mkd. T32S R4W S32 BT.

A Fir 40" dia., bears N.58°W., 92 lks. dist., mkd. T32S R4W S29 BT.

This cor. is on a steep hillside, sloping W., 25 ft. below spur.

George J. Wenderoth - 1946-47 - (No record source found, information from previous renewal records, #25)

-----  
Found original bearing trees:

40" Fir bearing N.58°W., 60.7ft.

Stump 36" Fir bearing S.13°W., 13.8 ft.

Stump 36" Fir bearing S.34°E., 41.8 ft.

Set 1" I.Pipe for the corner and mkd. the following BTs:

6" Fir bearing N.54°33'W., 25.5 ft.

8" Madrona bearing N.9°30'E., 42.5 ft.

10" Madrona bearing S.47°40'E., 29.0 ft.

No tree available in Sec. 32.