

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8521)

-----  
Set a Fir post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. corner, marked ¼ S on W. face; from which  
A dead Fir 24" dia., bears N.42°E., 18 lks. mkd. ¼ S BT.  
A dead Fir 20" dia., bears N.73°W., 27 lks. mkd. ¼ S BT.

Survey by James D. Artman - For: Medford Corporation - April 1990 - M 110-11

-----  
Set 5/8" x 30" Iron rod with 1" plastic cap mkd. ARTMAN RLS 2268.  
BTs - 9" Live Oak bears S.27°W., 20.2 ft. scribed ¼ S29 BT.  
14" Madrone bears S.20°E., 18.6 ft. scribed ¼ S28 BT.  
15" D.Fir bears N.35°E., 30.8 ft. scribed ¼ S28 BT.  
6" D.Fir bears N.45°W., 31.0 ft. scribed ¼ S29 BT.

Ron Quimby For: Silver Butte Tbr Co. - July 2019 - M175-78A-B

-----  
Found - 5/8" iron rod per M110-11  
9" Oak bears S.27°W 20.2'  
15" Madrone bears S.20°E 18.6'  
20" Fir bears N.35°E., 30.8'  
10" Fir bears N.45°W., 31.0'  
7" dead oak bears N.14°W., 39.5' with tag **NO RECORD**