

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8521-22)

-----  
Set a Madrona post, 3 ft. long, 4" sq., 24" in the ground for a corner of secs. 20, 21, 28 and 29, marked T32S S21 on NE.; R4W S28 on SE.; S29 on SW.; and S20 on NW. faces, with 2 notches on S. and 4 notches on E. edges; from which

A Fir 48" dia., bears N.23°E., 168 lks. mkd. T32S R4W S21 BT.

A dead Fir 30" dia., bears S.33°E., 89 lks. mkd. T32S R4W S28 BT.

A dead Fir 36" dia., bears S.22°W., 128 lks. mkd. T32S R4W S29 BT.

A Fir 30" dia., bears N.23°W., 165 lks. mkd. T32S R4W S29 BT.

This corner is on the E. slope of ridge, about 75 ft. below top.

George J. Wenderoth - Deputy Co. Surveyor - April 14, 1947 - C.S. File 38/246-1

-----  
Found original bearing trees:

48" Fir bearing N.23°E., 110.8 ft.

Stump bearing S.33°E., 58.7 ft.

Stump bearing N.23°W., 108.9 ft.

Set 1¼" I.Pipe for the cor. and marked the following BTs:

5" Chinquapin bearing N.34°33'W., 22.3 ft.

8" Fir bearing S.80°W., 5.6 ft.

4" Madrone bearing N.9°09'E., 35.9 ft.

5" Madrone bearing S.48°04'E., 21.5 ft.

Fd. ok by Kris DeGroot- 1/2005 - M 146-16

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2141, surveyed April/July 2006 - (DCSO records Vol. 55 Page(s) 21393)

-----  
The corner of secs. 20, 21, 28, & 29, perpetuated from original evidence, no longer in existence, by Wenderoth, in 1947, monumented with an iron pipe 1¼" dia., firmly set, projecting 15" above the ground.

from which bearing trees marked by Wenderoth

A madrone, 10" dia., bears S.48¼°E., 20.5 ft., with a healed blaze.

A D.Fir, 30" dia., bears S.83¾°W., 5.8 ft., with a healed blaze.

continued next page

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A chinquapin snag, 11" dia., bears N.35¼°W., 23.0 ft.,  
with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the  
ground, directly over the iron pipe, with brass cap mkd.

T 32 S R 4 W

S 20 | S 21

S 29 | S 28

2006

from which new bearing trees

A D.Fir, 15" dia., bears N.45°E., 18.4 ft., mkd. T32S R4W  
S21 BT.

A chinquapin, 6" dia., bears N.52¾°W., 50.4 ft., mkd. X at  
breast height, BT at the base.

Ron Quimby For: Silver Butte Tbr Co. - July 2019 - M175-78A-B

-----

Found - Brass cap per 2006 BLM Dependent resurvey  
10" Madrone bears S.48¼°E., 20.5' with healed blaze  
31" Fir bears S.83¾°W., 5.8' with healed blaze  
16" Fir bears N.45°E., 18.4'  
6" chinquapin bears N.52¾°W 50.4'

New BTs- 7" Madrone bears N.18°W., 41.0' scribed "T32S R4W  
S20BT"