



PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2141, surveyed April/July 2006 - (DCSO records Vol. 55 Page(s) 21394-5)

-----  
The ¼ sec. cor. of secs. 20 & 21, perpetuated by Wenderoth, in 1947, further perpetuated by Theilsen, monumented with an iron post 2½" dia., firmly set, projecting 8" above the ground, with a brass cap (properly) mkd. from which bearing trees mkd. by Wendroth and reported by Theilsen

A D.Fir, 35" dia., bears S.61°E., 11.9 ft., with a healed blaze.

A sawed incense cedar stump, 34" dia., bears N.15°W., 33.7 ft., with no visible marks. (Record, 40.3 ft.) and a new bearing tree

A D.Fir, 6" dia., bears N.10°W., 25.2 ft., mkd. ¼ S21 BT. The iron pipe 1¼" dia., set by Wenderoth, and projecting 4" above the ground, is set alongside the iron post. The original wood post is firmly set 9" N. of the iron post, and projects 21" above the ground, with scribe marks 1/4S visible on its W. face.

Ron Quimby - Crew: N. Fromdahl & J. Ogden - 6/2019 - C.S. File 65/102-59

-----  
Found - BLM brass cap (properly mkd)  
39" Fir S.61°E., 11.9 ft. good scar.  
34" Cedar stump N.15°W., 33.7 ft. (face cut out)  
7" D.Fir N.10°W., 25.2 ft. faint scar.  
New - 24" D.Fir N.39°E., 13.0' scribed ¼ S21 BT.  
15" D.Fir N.60°W., 17.0' scribed ¼ S20 BT.  
Note - Compass decl. 15½°E.