

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8524-25)

Set a Madrona post, 3 ft. long, 4" sq., 24" in the ground for a corner of secs. 16, 17, 20 and 21, marked T32S S16 on NE.; R4W S21 on SE.; S20 on SW.; and S17 on NW. faces, with 4 notches on E. and 3 notches on S. edges, from which
A Madrona 8" dia., bears N.27°E., 41 lks. mkd. T32S R4W S16 BT.
A Live Oak 6" dia., bears S.68°E., 27 lks. mkd. T32S R4W S21 BT.
A Madrona 8" dia., bears S.85°W., 18 lks. mkd. T32S R4W S20 BT.
A Madrona 6" dia., bears N.81°W., 21 lks. mkd. T32S R4W S17 BT.

This corner is on the S. slope of spur, 200 ft. above ravine.

George J. Wenderoth, Deputy Co. Surveyor - 1947-48 - C.S. File 38/246

Found - 18" Madrona, bearing N.26°E., 26.0 ft.
Set 1¼" I.Pipe for corner and mkd. the following BTs:
8" Fir bearing N.82°45'E., 51.2 ft.
14" Fir bearing S.78°34'E., 38.7 ft.
30" B.Oak bearing N.60°45'W., 91.1 ft.
16" Fir bearing S.12°20'W., 44.9 ft.

BLM resurvey by Larry Evans, Cadastral Surveyor under Group #736, surveyed May/June 1971 (DCSO records Vol. 37 Page(s) 15342-43)

The Sec. cor., perpetuated and recorded by Wenderoth in 1947, monumented with an iron pipe 1¼" dia., protruding 15" above the ground, firmly set, at record bearing and distance from the remaining 1897 bearing trees:

A Madrone 21" dia., bears N.27°E., 37½ lks. dist., with healed blaze. (Record, and to face, 41 lks.)
A Madrone 13" dia., bears N.81°W., 21 lks. dist., with opened and decayed blaze.
and bearing trees mkd. by Wenderoth
A Fir 10" dia., bears N.81½°E., 78 lks. dist., with healed double blaze.
A Fir 18" dia., bears S.80 3/4°E., 59½ lks. dist., with healed double blaze.
A Fir 24" dia., bears S.11¼°W., 67 lks. dist., with healed double blaze.

(Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. cor. for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A B.Oak 34" dia., bears N.61½°W., 140 lks. dist., with
healed double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,
with brass cap mkd: T 32 S R 4 W

S 17 | S 16

S 20 | S 21

1971

Deposit iron pipe alongside iron post.

Fd Ok by R. Quimby, 6/2019 - C.S. File 65/105-58