

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8527-28)

Set a Madrona post, 3 ft. long, 4" sq., 24" in the ground for a corner of secs. 8, 9, 16 and 17, marked T32S S9 on NE.; R4W S16 on SE.; S17 on SW.; and S8 on NW. faces, with 4 notches on S. and E. edges; from which
A Fir 12" dia., bears N.87°E., 131 lks. mkd. T32S R4W S9 BT.
A Fir 10" dia., bears S.68°E., 71 lks. mkd. T32S R4W S16 BT.
A Fir 12" dia., bears S.56°W., 150 lks. mkd. T32S R4W S17 BT.
A Madrona 6" dia., bears N.40°W., 77 lks. mkd. T32S R4W S8 BT.

This corner is on the southerly slope of ridge, 100 ft. above ravine.

George J. Wenderoth, Deputy Co. Surveyor - Wit: Frank Loso - April 1948 - (No record source found. Infor. taken from former renewal #38)

Find old BTs:
30" Fir N.87°E., 86.4 ft.
30" Fir S.68°E., 46.8 ft.
30" Fir S.56°W., 99.0 ft.
Drive a 1" iron pipe and mark new BT:
8" Madrona N.66°45'W., 21.4 ft.

BLM resurvey by Larry Evans, Cadastral Surveyor under Group #736, surveyed May/June 1971 (DCSO records Vol. 37 Page(s) 15347-48)

The Sec. cor., perpetuated and recorded by Wenderoth in 1948, monumented with an iron pipe, 1" dia., protruding 6" above the ground, firmly set, at record distance from the remaining 1897 bearing trees:
A Fir 33" dia., bears N.83°E., 131 lks. dist., with healed blaze. (Rec. N.87°E.)
A Fir 41" dia., bears S.68°E., 71 lks. with scribe marks S16 visible on partially opened blaze.
A Fir 51" dia., bears S.56°W., 150 lks. with healed blaze.
and a bearing tree mkd. by Wenderoth:
A Madrone 9" dia., bears N.68°W., 33 lks. dist., with scribe marks S8 CS BT visible on partially healed double blaze.

At the corner point (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. cor. for 8, 9, 16 and 17

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground directly over the iron pipe, with brass cap mkd:

T 32 S R 4 W	
S 8	S 9
S 17	S 16
1971	

Fd. OK, Nov. 1990, M 111-12

Mark Smalley, Roseburg Forest Products - Party Chief: William Olson - May 2009 - C.S. File 65/66-30

Found - 1971 BLM brass cap.
 39" Douglas fir N.86°E., 87.2' Healed blaze 1896 (Rec N.83°E., 86.46')
 45" Douglas fir S.68°E., 47.0' Stump 1896
 54" Douglas fir S.56°W., 99.0' Stump 1896
 10" Madrone N.65°W., 21.5' (Rec N.68°W., 21.78') Stump 1948

New - 11" D.Fir N.2°W., 12.9' measured to a nail in the side-center of stump Scribed "S8BT" with LS 2354 brass washer
 9" D.Fir S.81°W., 20.5' measured to a nail in the side-center of stump Scribed "S17BT" with LS 2354 brass washer
 5" D.Fir S.60°E., 15.2' measured to a nail in the side-center of stump Scribed "S16BT" with LS 2354 brass washer

Note - Compass decl. 18°E.

BLM Dependent resurvey by Ernest Q. Lundeen, Cadastral Surveyor, under Group No. 2790, surveyed July 2015 - (DCSO records Vol. 58 Page(s) 23436-7)

The cor. of secs. 8, 9, 16, & 17, perpetuated by Smalley, in 2009; monumented with an iron post, 2½" dia., firmly set, projecting 4" above the ground, with brass cap (properly) mkd.
 from which the remains of original bearing trees
 A fir, 41" dia., bears N.83¾°E., 87.6 ft., with a healed blaze. (Record, N.83°E., 86.5 ft.)
 A sawed fir stump, 46" dia., bears S.68°E., 46.9 ft., with open rotted blaze.
 and the remains of a BT mkd. by Wendroth, in 1948, as reported by Evans in 1971.
 A sawed madrone stump, 10" dia., bears N.68°W., 21.8 ft., with a rotted blaze.

continued next page

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

and bearing trees mkd. by Smalley

A fir, 6" dia., bears S.58°E., 14.9 ft., with a washer mkd. LS 2354 in healed blaze and an aluminum nail right side center.

A fir, 10" dia., bears S.79½°W., 20.4 ft., with a washer mkd. LS 2354 in partially healed blaze.

A fir, 11" dia., bears N.2¼°W., 12.6 ft., with a washer mkd. LS 2354 in partially healed blaze and an aluminum nail left side center.