

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 300531

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 8 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Survey by H.W. Laurence - March 1949 - C.S. File 40/174 ----- Set a 4" Fir post, 4 ft. long, firmly in the ground, scribed ¼ S8, also crayoned marked 1543, from which 12" Fir bears N.33°W., 32.4 ft. scribed ¼ S8 BT. 42" Fir bears S.55°W., 41.6 ft. scribed ¼ S8 BT.</p>
<p>Survey by Kristian DeGroot, L.S. #1941 - For: Roseburg Resources and S. Jantzer - Nov. 1990 - C.S. File 63/52 and M 111-12 ----- Set 1" x 30" Iron pipe, 24" in the ground with brass cap mkd. "T32S R4W ¼ S8 1990 PLS 1941" BTs by Laurence in 1949: 24" D.Fir bears N.33°W., 32.4 ft. with healed blaze. 54" D.Fir bears S.55°W., 41.6 ft. with a healed blaze.</p>
<p>Mark Smalley - For: Roseburg Resources - 11/ 2005 thru 1/2006 - M150-7 ----- Found - 1990 IPBC marked PLS 1941 24" D.Fir N.33°W., 32.4', good cond. Healed face. 54" D.Fir S.55°W., 41.6', good cond. Healed face Scribed: "¼ S8 BT" 10" D.Fir N.59°W., 6.8' 25" D.FIR N7°W., 25.2'</p>
<p> </p>