

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 9 only

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8529-30)

-----  
Set a Fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. corner, marked ¼ S on W. face; from which  
A Fir 16" dia., bears N.85°E., 7 lks. mkd. ¼ S BT.  
A Fir 12" dia., bears N.85°W., 13 lks. mkd. ¼ S BT.  
This corner is on the N. slope of spur, 100 ft. below top.

Survey by Kristian DeGroot, L.S. #1941 - For: Roseburg Resources and S. Jantzer - Nov. 1990 - C.S. File 63/52 and M 111-12

-----  
Set 1" x 30" Iron pipe 24" in the ground with a 2½" brass cap.  
BTs - 38" D.Fir bears N.85°E., 4.6 ft. with healed blaze. (Original)  
21" D.Fir bears N.85°W., 8.6 ft. with healed blaze. (Original)

Mark Smalley - For: Roseburg Resources - 11/ 2005 thru 1/2006 - M150-7

-----  
Found - 1990 IPBC, marked PLS 1941  
36" D.Fir N.85°E., 4.6', good cond. healed face.  
25' D.Fir N.85°W., 8.6', good cond. healed face  
Scribed "¼ S9 BT"  
17" D.Fir N.58°E., 22.9'  
10" D.Fir N.85°W., 26.5'