

PRIMARY CORNER DESCRIPTION Sec. Cor. 4 & 5 only, on N. bdy. Sec. 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8458)

Set post corner to secs. 4, 5, 8 and 9, from which
A Cedar 15" dia., bears N.40°E., 56 lks. dist.
A Yew 14" dia., bears S.70°E., 70 lks. dist.
A Fir 36" dia., bears S.25°W., 311 lks. dist.
A Fir 40" dia., bears N.45°W., 43 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8531)

The cor. of secs. 4, 5, 8 and 9, which is a post 4" sq., marked and witnessed as described by the surveyor general. I reestablish this corner as follows:
Set a Fir post, 4" sq., 4 ft. long, 24" in the ground for corner of secs. 4 and 5, marked T32S S4 on NE.; and R4W S5 on NW.; faces, with 4 notches on E. edge; from which
A Cedar 16" dia., bears N.40°E., 56 lks. dist., mkd. T32S R4W S4 BT.
A Fir 40" dia., bears N.45°W., 43 lks. dist., mkd. T32S R4W S5 BT.

George J. Wenderoth, Deputy Co. Surveyor - Wit: F. Loso - April 1950 - C.S. File 40/246

Found - 20" Cedar N.40°E., 37.0 ft.
48" Fir N.45°W., 28.4 ft.
Drive 1" Iron pipe for corner.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12800-01)

The cor. of secs. 4 and 5, on the N. bdy. of sec. 9, determined at record bearing and distance from each of the remaining original bearing trees:
A Yew 16" dia., bears S.70°E., 70 lks. dist., marked with portions of scribed marks on open blaze.
A Fir 40" dia., bears N.45°W., 43 lks. dist., marked S5 T32S R4W BT on bark.
At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked
(Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. cor. 4 & 5 only, on N. bdy. Sec. 9

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

T32S R4W S 5 S 4 S 9 1959
from which new bearing trees A Fir 12" dia., bears N.43°E., 72 lks. dist., mkd. T32S R4W S4 BT. A Fir 7" dia., bears N.18¼°W., 107 lks. dist., mkd. T32S R4W S5 BT.
Fd. OK, B. Shaner, 1963 - RM 1-37
Troy Rambo - For: Seneca Jones Timber - July 2002 - M140-74 ----- Found - 1959 BLM Brass Cap 42" DF - bears N.45°W., 43 lks. 21" Yew - bears S.70°E., 70 lks. 15" WH (rec. DF) bears N.18¼°W., 71.00 ft. (107 lks) Scribed- "T32S R4W S4 BT" on an 8" DF, bears N.49°E., 16.8 ft
Mark Smalley - For: Roseburg Resources - 11/ 2005 thru 1/2006 - M150-7 ----- Found - 1959 CAD. IPBC 7" D.Fir N.49°E., 16.8', (record 8" D.Fir N.49°E., 16.8') Good cond. Scribe visible. 14" Hemlock N.18½°W., 71.0' Good cond, healed face. 19" Yew S.70°E., 46.2' (Rec. 21" Yew S.70°W., 46.2') Good cond, open face. 50' D.Fir N.45°W., 28.4' good cond, no marks visible