

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8471)

Set a basalt stone 14 x 10 x 6 ins., 9" in the ground for ¼ sec. corner, mkd. ¼ on N. face, from which
A Live Oak 8" dia., bears S.38°E., 14 lks. mkd. ¼ S BT.
A Fir 40" dia., bears N.63°W., 15 lks. mkd. ¼ S BT.
This ¼ sec. cor. is on a hillside sloping W., about 800 ft. below sec. corner.

Survey by Ronald A. Brandt - For: Robert Dollar Co. - Oct. 1969 - C.S. File 55/129-1

Found - Orig. 40" D.Fir now 40" low cut stump, N.63°W., 15 lks., opened prior to logging, about 1955, and some scribing remains on the stump and on a piece of wood layed by the stump, "¼".
Set 3/4" x 32" Iron pipe.
Scribed -10" Madrone N.19½°E., 16.6 ft. mkd. T32S R4W S28 RS841 BT.
5" Madrone S.78°W., 11.0 ft. mkd. T32S R4W S33 RS841 BT.

Adam DeGroot - For: Silver Butte Timber Co. - June 2019 - M171-59

Found - A ¾" I.D. iron pipe by R. Brandt, in 1969 firmly set & projecting 6" above the ground:
From which the remains of an original 1897 BT:
A 40" rotted D.Fir stump bears N.62°W., 11.6 ft, no mks visible (N.63°W., 15 lks)
and BTs by Brandt in 1969:
A 17" Madrone bears N.18°45'E., 16.2 ft w/illegible scribe mks. on partially healed blaze (N.19°30'E., 16.6 ft)
A 9" Madrone bears S.78°15'W., 11.0 ft w/healed blaze (S.78°W., 11.0 ft)
New BTs- A 26" D.Fir bears S.42°45E., 29.4 ft scribed "¼ 33 BT" on dbl blaze.
A 11" D.Fir bears N.21°15'W., 23.7 ft scribed "¼ S28 BT" on dbl blaze.

NAD83 (2011) EPOCH 2010.00 GEODETIC COORDINATES:
LATITUDE 42°45'21.57658"N LONGITUDE 123°10'54.91207"W