

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 (DCSO rec Vol 20 Pages 8522-23)

-----  
Set a Madrona post 3 ft. long, 4" sq., 24" in the ground for 1/4 sec. corner, marked 1/4 S on N. face; from which  
A Fir 20" dia., bears N.75°E., 44 lks. mkd. 1/4 S BT.  
A Fir 24" dia., bears S.87°E., 36 lks. mkd. 1/4 S BT.  
This corner is on the N slope of spur, 150 ft above Boulder Creek

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, W. Penley, crew - May 5, 1970 - C.S. File 54/114-9

-----  
Found - 20" D.Fir, now stump, N.75°E., 29.0 ft., opened for scribe "T"  
24" D.Fir, now stump, S.87°E., 23.8 ft., opened earlier, scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office  
T 32 S R 4 W  
1/4 S 21  
S 28  
1970

New BTs -5" Live Oak N.62 1/4°E., 25.5 ft. mkd. 1/4 S21 CS BT.  
5" Live Oak N.2°E., 38.0 ft. mkd. 1/4 S21 CS BT.  
This corner lies in logged unit, no other BTs available.

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2141, surveyed April/July 2006 - (DCSO records Vol. 55 Page(s) 21392-3)

-----  
The 1/4 section corner of sections 21 and 28, perpetuated by the Douglas County Surveyor's Office in 1970, recorded per file C.S. 54/114, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above the ground, with a brass cap (properly) mkd.,

from which the remains of the original bearing trees  
A decayed D.Fir stump of indeterminate size, bears N.75°E., 29.0 ft., with scribe mark T visible on an open rotted blaze.

A decayed D.Fir stump of indeterminate size, bears S.87°E., 23.8 ft., with scribe mark S visible on an open rotted blaze.

and BTs mkd. by the Douglas County Surveyor's Office

A live oak, 9" dia., bears N.3 1/2°E., 37.1 ft., with a healed blaze.

A live oak, 10" dia., bears N.61 1/4°E., 25.3 ft. with a healed blaze. \_\_\_\_\_ CONT.

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Adam DeGroot - For: Silver Butte Timber Co. - June 2019 - M171-59

-----

Found - A 1¼" iron post by DCSO in 1970 per, firmly set and projecting 12" above ground, w/a 2½" brass cap properly marked per the record:

From which the remains of the original 1897 BTs:

A rotted D.Fir stump bears N.75°E., 29.0 ft w/scribe mks "T" visible on open blaze (N.75°E., 44 lks) (29.0 ft)

A rotted D.Fir stump bears S.87°E., 23.8 ft w/scribe mks "S" visible on open blaze (S.87°E., 36 lks) (23.8 ft)

And BTs by DCSO in 1970:

A 9" Live Oak bears N.3°30'E., 37.1 ft w/healed blaze (N.2°E., 38.0 ft) (N.3°30'E., 37.1 ft)

A 10" Live Oak bears N.61°45'E., 25.3 ft w/healed blaze (N.62°15'E., 25.5 ft) (N.61°45'E., 25.3 ft)

NAD83 (2011) EPOCH 2010.00 GEODETIC COORDINATES:

Latitude 42°46'13.46169"N Longitude 123°10'55.58442"W