

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 4 only

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8458)

-----  
Set ¼ sec. post, from which  
A Fir 10" dia., bears N.22°W., 30 lks. dist.  
A Fir 40" dia., bears South, 7 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8531)

-----  
The ¼ sec. corner; post destroyed; bearing trees standing, from which I reestablish this corner as follows:  
Set a Fir post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on N. face; from which  
A Fir 10" dia., bears N.22°W., 30 lks. dist., mkd. ¼ S BT.  
A Fir 40" dia., bears South, 7 lks. dist., mkd. ¼ S BT.

GLO resurvey by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO rec. Vol. 30 Page(s) 12778)

-----  
The ¼ sec. cor. of sec. 4 only, determined at record bearing and distance from the original bearing trees mkd. by Byars in 1871:  
A sawed Fir stump 16" dia., bears N.22°W., 30 lks. mkd. BT on bark.  
A Fir 40" dia., bears South, 7 lks., mkd. ¼ S BT on bark.  
At the corner point  
Set an iron post, 28" long, 2½" dia., 20" in the ground, with brass cap marked ¼ S 4  
T32S R4W  
1959  
from which new bearing trees  
A Fir 12" dia., bears N.3¼°E., 168 lks., mkd. ¼ S4 BT.  
A Fir 14" dia., bears N.49½°E., 76 lks. mkd. ¼ S4 BT.

Fd. BLM BC - by Troy Rambo, July 2002 M140-74