

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 372600

PRIMARY CORNER DESCRIPTION CC for Secs. 9 & 10 on S. bdy S. 4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8519)

-----  
I Set a Fir post, 3 ft. long, 4" sq., 24" in the ground, for a closing corner of secs. 9 and 10, marked C C T32S R4W on S.; S9 on W.; and S10 on E. faces, with 5 grooves on S. and 3 grooves on E. faces; from which

A Cedar 10" dia., bears S.40°E., 34 lks. dist. mkd. T32S R4W S10 BT.

A Madrona 10" dia., bears S.33°W., 31 lks. dist., mkd. T32S R4W S9 BT.

This corner is on a S. slope, 50 ft. above creek.

GLO resurvey by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO rec Vol. 30 Page(s) 12781-82)

-----  
Point for the closing cor. of secs. 9 and 10; at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked

S 4  
S 9 | S 10  
T32S | R4W  
C C  
1959

from which

A Fir 14" dia., bears S.32½°E., 48 lks. dist. mkd. T32S R4W S10 CC BT.

A Fir 14" dia., bears S.29°W., 55 lks. dist. mkd. T32S R4W S9 CC BT.

Fd. BLM BC & BTs by Troy Rambo, July 2002 M140-74

Fd. Ok by T Hostetter, 4/2006 - M150-60