

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8470)

-----  
Set a basalt stone 12 x 10 x 8 ins., 8" in the ground, for cor. of secs. 27, 34, 33 and 28, mkd. with 3 notches on W., and 3 notches on E. edges; from which  
A dead Fir 14" dia., bears N.66°E., 60 lks., dist., mkd. T32S R4W S27 BT.  
A dead Fir 14" dia., bears S.86°E., 44 lks. dist. mkd. T32S R4W S34 BT.  
A dead Fir 12" dia., bears S.45°W., 77 lks. dist. mkd. T32S R4W S33 BT.  
A Fir 40" dia., bears N.7½°W., 203 lks. dist. mkd. T32S R4W S28 BT.

Survey by Ronald A. Brandt - For: Robert Dollar Co. - Oct. 1969 - C.S. File 55/129-1

-----  
Found - Remains of orig. dead D.Fir 14", S.86°E., 44 lks., the snag had broken off at the ground and left a distinct stump, scribing on the felled portion "S34 BT". Using the above bearing and distance, the pipe was set.  
Set 3/4" x 32" Iron pipe.  
Scribed -11½" D.Fir S.41°E. 50.1 ft mkd T32S R4W S34 RS841 BT  
9" D.Fir N.19°E., 48.5 ft. mkd T32S R4W S27 RS841 BT  
12" D.Fir N.45°W., 71.7 ft mkd T32S R4W S28 RS841 BT  
4" Live Oak S.40°W., 36.2 ft. mkd. S33 BT.

Adam DeGroot - For: Silver Butte Timber Co. - June 2019 - M171-59

-----  
Found - A ¾" I.D. iron pipe by R. Brandt, in 1969, firmly set into solid fractured rock, projecting 16" above ground and leaning southeasterly. I straighten to plumb and construct  
A 24" dia. x 8" high stone mound. pipe now projects 8" above stone mound:  
From which the remains of a original 1897 BT:  
A 14" rotted D.Fir stump bears S.85°30'E., 29.8 ft w/no mks visible (S.86°E., 44 lks)  
And BTs by Brandt in 1969:  
A 27" D.Fir bears N.19°45'E., 48.5 ft w/healed blaze (N.19°E., 48.5 ft)  
A 25" D.Fir bears S.40°E., 49.9 ft w/healed blaze (S.41°E., 50.1 ft)

continued next page

