

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8509-10)

Set a basalt stone 14 x 10 x 8 ins., 9" in the ground for ¼ sec. corner, marked ¼ S on W. face; from which
A Fir 20" dia., bears N.50°E., 6 lks. mkd. ¼ S BT.
A Fir 24" dia., bears N.83°W., 7 lks. mkd. ¼ S BT.
This cor. is on the SW. slope of spur, 25 ft. above Boulder Creek.

Survey by Ronald A. Brandt - For: Robert Dollar Co. - Oct. 1969 - C.S. File 55/129-1

Found - 24" now 28" orig. D.Fir N.83°W., 7 lks., blown down. I opened the face additionally and found the scribing "¼S"
Orig. 20" now 24" D.Fir N.50°E., 6 lks., good condition. Upper face opened about 1954 but couldn't read any scribing. Opened lower, chopped in 2-3", and found the scribing "¼S".
Set 3/4" x 32" Iron pipe.
Scribed -16" Yewwood S.14½°W., 29.2 ft. mkd. T32S R4W S28 RS841 BT.

Adam DeGroot - For: Silver Butte Timber Co. - June 2019 - M171-59

Found - A ¾" I.D. iron pipe by R. BRANDT, in 1969, firmly set & projecting 4" above the ground:
From which the original 1897 BTs:
A 30" D.Fir bears N.44°15'E., 4.5 ft w/re-healed dbl blaze (N.50°E., 6 lks)
The root hole of a down & rotting 28" D.Fir bears record (N.83°W., 7 lks)
And a BT by Brandt in 1969:
A 18" Yewwood bears S.15°W., 29.7 ft w/scribe mks "T32SR4WS28RS841BT" visible on open blaze (S.14°30'W., 29.2 ft)
New BTs- A 7" D.Fir bears S.53°45'E., 38.1 ft scribed "¼S27 BT" on dbl blaze.
A 12" D.Fir bears S.57°45'W., 21.0 ft scribed "¼S28 BT" on dbl blaze.
NAD83 (2011) EPOCH 2010.00 GEODETIC COORDINATES:
Latitude 42°45'47.39643"N Longitude 123°10'19.47377"W