

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8510)

Set a Madrona post 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 21, 22, 27 and 28, marked T32S S22 on NE.; R4W S27 on SE.; S28 on SW.; and S21 on NW. faces, with 3 notches on E. and 2 notches on S. edges; from which
A Pine 48" dia., bears N.64°E., 25 lks mkd T32S R4W S22 BT
A Fir 24" dia., bears S.10°E., 51 lks. mkd T32S R4W S27 BT
A Fir 20" dia., bears S.9°W., 26 lks. mkd. T32S R4W S28 BT
A Fir 48" dia., bears N.60°W., 58 lks. mkd T32S R4W S21 BT
This corner is on the NE. slope of spur, 75 ft. below top.

Survey by H.L. Eppstein, July 1937, Made by Bart Lane - M 6-6

Corner found.
48" Pine N.64°E., 25 lks.
20" Fir S.9°W., 26 lks.
48" Fir N.60°W., 58 lks.
48" Fir S.62°E., 62.0 feet.

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - May/Aug. 1954 - C.S. File 41/302

Determined at the record bearing and distance from the original NE., SW., and NW. bearing trees and record bearing from the original SE. bearing tree.
Set an Iron pipe 3 ft. long, 2" dia., 28" in the ground mkd. RS33, from which the original bearing trees:
A Sugar Pine 48" dia., bears N.64°E., 25 lks. mkd. T32S R4W S22 CS BT.
A Fir stump 26" dia., bears S.10°E., 61 lks. with no marks remaining.
A Fir stump 34" dia., bears S.9°W., 26 lks. with no marks remaining.
A Fir stump 52" dia., bears N.60°W., 58 lks. with no marks remaining.
And a bearing tree mkd. by the County Surveyor:
A D.Fir 36" dia., bears S.30½°E., 99 lks. mkd. T32S R4W S27 CS BT.

Fd. OK, Greg Lang, July 1995 - M 122-46

continued next page

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

David Edwards - For: Seneca Jones Timber Co. & Plum Creek
Timberlands - 11/2010 - M161-51

Section corner as per M122-46
Found - 2" IP mkd RS33
48" Fir S.30½°E., 65.3' with healed blaze.
New BTs- 7" Fir S.38°W., 1.1' scribed S28 BT.
13" Madrone N.45°W., 15.95' scribed S21 BT.
Set - 6 ft. steel post 2 ft. North.

Adam DeGroot - For: Silver Butte Timber Co. - June 2019 -
M171-59

Found - A 1¾" I.D. iron pipe by N. Price, in 1954 firmly set
and projecting 12" above ground, leaning north
±0.3' from plumb:
From which the remains of original 1897 BTs:
A 48" rotted S.Pine stump bears N.63°E., 16.0 ft
w/no mks visible (N.64°E., 25 lks)
A 40" D.Fir stump bears S.11°W., 17.0 ft w/ no mks
visible on open blaze (S.9°W., 26 lks)
And a BT by DCS0:
A 49" D.Fir bears S.28°15'E., 65.9 ft w/healed blaze
(S.30°30'E., 99 lks)
And BTs by Edwards in 2010 per M 161-51:
A 12" D.Fir saw stump bears S.38°W., 1.1 ft w/healed
lower blaze (S.38°W., 1.1 ft)
A 13" Madrone bears N.46°30'W., 15.9 ft w/scribe mks
"T32R4WS21BT" on open single blaze (N.45°W.,
15.95 FT)
New - A MAG-HUB & brass washer in top of a sawn 12" D.Fir
stump bears N.48°33'E., 15.72 FT.
A 7" D.Fir bears S.56°30'W., 14.9 ft scribed
"T32SR4WS28 BT" on dbl blaze.
NAD83 (2011) EPOCH 2010.00 GEODETIC COORDINATES:
Latitude 42°46'13.41356"N Longitude 123°10'19.91913"W