

PRIMARY CORNER DESCRIPTION ¼ cor of 21 & 22

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original GLO by Carl S. Nicklin, Deputy Surveyor - Contract 664, dated May 23, 1896 - (DCSO records Vol. 20 Page(s) 8512)

Set - Fir post, 3' long 4" sq., 24" in ground, mkd. ¼S. on W. face.
BT's - Fir, 30" dia., bears N.55°E., 9 lks., mkd. ¼ S., B. T. Maple, 10" dia., bears S.80°W., 62 lks. mkd. ¼ S., BT

H.L. Eppstein, County Surveyor - July 1937 - for: Clare Lumber Co. - M6-6

Found - ¼ corner post
BT's - 30" Fir, N.70°E., 44 lks.
10" Maple, S.80°W., 62 lks.

Greg Lang, July 1995, M122 - 46

Found - BLM location tag on bark from decomposing stump 7/13/53 "BH MCGILLICUDDY" (no rec.)
BT Tag by Schwartz on bark from decomposing stump "2-12-68" "S55°W" 6' "Schwartz". (no rec.)
A clump of small maples bears approx. S.80°W., 40.92' 10' tree seems to be gone.
49" Fir, with a location tag, bears N.28°W., 23.5' (to face) "HW" cut into bark on easterly side of tree. BLM location tag 2-12-68 "S.25°E., 24' "Schwartz" "Hand Compass & Tape". (no rec.)
Set - 5/8" x 30" I.R. w/plastic cap mkd. "Lang Surveying"
New BTs- 8½" Fir, bears N.84°21'E., 37.10 (scribed "¼ S22 BT").
18" Fir, bears S.52°18'W., 24.68' (scribed "¼ S21 BT").
6½" Fir, bears N.15°57'W., 14.86' (scribed "¼ S21 BT").
8½" Fir, bears S.21°08'E., 38.57' (scribed "¼ S22 BT").

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2141, surveyed April/July 2006 - (DCSO records Vol. 55 Page(s) 21397-8)

The ¼ sec. cor. of secs. 21 & 22, perpetuated by Lang, in 1995, and monumented with an iron rod, 5/8" dia., firmly set, projecting 5" above the ground, with a plastic yellow cap mkd. LANG SURVEYING.
from which the remains of an original bearing tree
A decayed Douglas fir stump of indeterminate size, bears N.55°E., 5.9 ft., no marks visible. cont.....

PRIMARY CORNER DESCRIPTION ¼ cor of 21 & 22

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

and bearing trees mkd. by Lang
A D.Fir, 11" dia., bears N.84¼°E., 37.4 ft., with a healed double blaze.
A D.Fir, 10" dia., bears S.21½°E., 38.8 ft., with a healed double blaze.
A D.Fir, 24" dia., bears S.54½°W., 25.0 ft., with a healed double blaze.
A D.Fir, 9" dia., bears N.17½°W., 15.3 ft., with a healed double blaze.
And a tree with a locator tag with the name SCHWARTZ on it and dated February 12, 1968
A D.Fir snag, 54" dia., bears N.27¾°W., 24.1 ft., no marks visible.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the iron rod, in a collar of stone, with brass cap mkd. T 32 S R 4 W
1/4
S 21 | S 22
2006
Deposit a magnet in a white plastic case at the base of the stainless steel post.

Fd. cor. as per M122-46 by D. Edwards 11/2010 - M161-51