

PRIMARY CORNER DESCRIPTION Sec. cor. for 15, 16, 21 and 22

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8513)

-----  
Set a Fir post 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 15, 16, 21 and 22, marked T32S S15 on NE.; R4W S22 on SE.; S21 on SW.; and S16 on NW. faces, with 3 notches on S. and E. edges, from which  
A Madrona 12" dia., bears N.70°E., 46 lks. mkd. T32S R4W S15 BT.  
A Fir 16" dia., bears S.60°E., 67 lks. mkd. T32S R4W S22 BT.  
A Fir 14" dia., bears S.34°W., 30 lks. mkd. T32S R4W S21 BT.  
A Fir 12" dia., bears N.63°W., 33 lks. mkd. T32S R4W S16 BT.  
This cor. is on the SW. slope of mountain, 100 ft. above ravine.

Survey by Norman D. Price, For: Dollar and Patterson Lumber Co. - May/Aug. 1954 - C.S. File 41/302

-----  
Determined at the record bearing and distance from each of the original bearing trees.  
Set an Iron pipe 3 ft. long, 2" dia., 28" in the ground mkd. "RS33"; from which the original bearing trees:  
A Madrona 18" dia., bears N.70°E., 46 lks. mkd. T32S R4W S15 with other blaze healed.  
A D.Fir 30" dia., bears S.60°E., 67 lks. with blaze healed.  
A D.Fir 27" dia., bears S.34°W., 30 lks. with blaze healed  
A D.Fir stump 16" dia., bears N.63°W., 33 lks. on which no marks remain.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12797-98)

-----  
The Sec. cor., determined at record bearing and distance from each of the original bearing trees:  
A Madrona 15" dia., bears N.70°E., 46 lks. mkd. T32S R4W S15, on opened blaze.  
A Fir 30" dia., bears S.60°E., 67 lks. dist., mkd. with a healed blaze.  
A Fir 30" dia., bears S.34°W., 30 lks. dist., marked with a healed blaze.

(Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir snag 24" dia., bears N.63°W., 33 lks. marked with a healed blaze.  
At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:     T32S R4W  
  S 16|S 15  
  S 21|S 22  
  1959  
from which new bearing trees  
A Fir 25" dia., bears N.44½°E., 91 lks. dist., marked T32S R4W S15 BT.  
A Fir 14" dia., bears N.44½°W., 139 lks. dist., marked T32S R4W S16 BT.

Fd. OK, Greg Lang, July 1995 - M122-46  
Fd. cor. as per M122-46 by D. Edwards 11/2010 - M161-51