

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8515-16)

Set a Madrona post, 3 ft. long, 4" sq., 24" in the ground for a corner of secs. 9, 10, 15 and 16, marked T32S S10 on NE.; R4W S15 on SE.; S16 on SW.; and S9 on NW. faces, with 3 notches on the E. and 4 notches on S. edges; from which

- A Fir 30" dia., bears N.33½°E., 100 lks. dist., mkd. T32S R4W S10 BT.
- A Fir 24" dia., bears S.43°E., 83 lks. dist., mkd. T32S R4W S15 BT.
- A Fir 36" dia., bears S.42°W., 240 lks. dist., mkd. T32S R4W S16 BT.
- A Fir 12" dia., bears N.75°W., 69 lks. dist., mkd. T32S R4W S9 BT.

This corner is in the bottom of ravine, sloping South 25 ft. below top of spur.

GLO resurvey by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Pgs 12780-81)

The Sec. cor., determined at record bearing and distance from the remaining original bearing trees:

- A fallen Fir 30" dia., bears S.43°E., 83 lks. dist., mkd. BT on opened blaze.
- A fallen Fir 18" dia., bears N.75°W., 69 lks. dist., mkd. S9 BT on opened blaze.

At the corner point
 Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:

T32S	R4W
S 9	S 19
S 16	S 15
1959	

from which new bearing trees

- A Fir 10" dia., bears N.84°E., 41 lks mkd. T32S R4W S10 BT
- A Fir 8" dia., bears S.32¼°E., 55 lks mkd. T32S R4W S15 BT
- A Fir 10" dia., bears S.5¼°W., 43 lks mkd. T32S R4W S16 BT
- A Fir 6" dia., bears N.28½°W., 16 lks. mkd. T32S R4W S9 BT

BLM Dependent resurvey by Ernest Q. Lundeen, Cadastral Surveyor, under Group No. 2790, surveyed July 2015 - (DCSO records Vol. 58 Page(s) 23435-6)

The cor. of secs. 9, 10, 15, & 16, monumented with an iron post, 2½" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd.
 continued next page

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

from which bearing trees mkd. by Thielsen in 1959
A fir, 23" dia., bears N.82 $\frac{3}{4}$ °E., 25.8 ft., with a healed blaze. (Record, N.84°E., 27.1 ft.)
A fir, 16" dia., bears S.27 $\frac{1}{2}$ °E., 36.9 ft., with a healed blaze. (Record, S.32 $\frac{1}{4}$ °E., 36.3 ft.)
A fir, 21" dia., bears S.5 $\frac{1}{4}$ °W., 28.4 ft., with a healed blaze.
A fir, 17" dia., bears N.24 $\frac{3}{4}$ °W., 9.9 ft., with a healed blaze. (Record, N.28 $\frac{1}{2}$ °W., 10.6 ft.)
NAD 1983 (2011)
Latitude: 42°47'56.78"N. Longitude: 123°10'18.49"W.